



PRODUCT DATA SHEET

3-36® Multi-Purpose Lubricant & Corrosion Inhibitor, 16 Fl Oz

No. 03007 | Item# 1003259 | Case# 1003258



Product Description

A versatile petroleum based compound that forms a clear, thin film that lubricates and protects against wear and corrosion. Multi-purpose product lubricates, protects, displaces moisture, and cleans.

Applications

Tubing, castings, gears, weld rod, wire, fixtures, dies, jigs, shim stock, chucks, drill rod, heat treated parts, machined surfaces, finished welds, aluminum extrusions, air actuated tools, conveyors, frozen joints, locks, hoists, etc.

Unit Package Description

16 Ounce Spray Bottle

Brand

CRC

Generic Description 1

Multi-Purpose Precision Lubricant & Corrosion Inhibitor

Net Fill

16 Fl Oz

UPC Code

078254030074

Unit Dimensions

9.38H x 2.75W x 3.75D in

Units Per Case

12

Case Dimensions

10.44H x 8.5W x 11.25D in

Cases Per Pallet

95

Case Weight

13 lbs

I 2 of 5 Code

30078254030075

Appearance

Clear Blue-Green Liquid

Base Type

Petroleum

Flash point (F)

192°F

Flash point (C)

89°C

Flammability Class - CPSC

None

Spec Gravity Concentrate

0.83

Plastic Safe

No

Film Type

Non-Drying

Film Thickness

0.025 to 0.075 Mils

Evaporation Rate

Slow

Last revised: 11/28/2017
Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Dielectric Strength	38,800 Volts
Working Temp (F)	-50 to 250°F
Working Temp (C)	-45.6 to 121.1°C
Propellant	None
NSF Category Code	H2
NSF Number	017429
Federal Specification Number	V-V-P-216,O-W-1284
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Multi-Purpose Lubricant
Removal (How To)	Remove with petroleum products, mineral spirits, or contact cleaner.

Last revised: 11/28/2017
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET

3-36® Multi-Purpose Lubricant & Corrosion Inhibitor, 16 Fl Oz

No. 03007 | Item# 1003259 | Case# 1003258



Product Description

A versatile petroleum based compound that forms a clear, thin film that lubricates and protects against wear and corrosion. Multi-purpose product lubricates, protects, displaces moisture, and cleans.

Applications

Tubing, castings, gears, weld rod, wire, fixtures, dies, jigs, shim stock, chucks, drill rod, heat treated parts, machined surfaces, finished welds, aluminum extrusions, air actuated tools, conveyors, frozen joints, locks, hoists, etc.

Unit Package Description

16 Ounce Spray Bottle

Brand

CRC

Generic Description 1

Multi-Purpose Precision Lubricant & Corrosion Inhibitor

Net Fill

16 Fl Oz

UPC Code

078254030074

Unit Dimensions

9.38H x 2.75W x 3.75D in

Units Per Case

12

Case Dimensions

10.44H x 8.5W x 11.25D in

Cases Per Pallet

95

Case Weight

13 lbs

I 2 of 5 Code

30078254030075

Appearance

Clear Blue-Green Liquid

Base Type

Petroleum

Flash point (F)

192°F

Flash point (C)

89°C

Flammability Class - CPSC

None

Spec Gravity Concentrate

0.83

Plastic Safe

No

Film Type

Non-Drying

Film Thickness

0.025 to 0.075 Mils

Evaporation Rate

Slow

Last revised: 11/28/2017
Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Dielectric Strength	38,800 Volts
Working Temp (F)	-50 to 250°F
Working Temp (C)	-45.6 to 121.1°C
Propellant	None
NSF Category Code	H2
NSF Number	017429
Federal Specification Number	V-V-P-216,O-W-1284
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Multi-Purpose Lubricant
Removal (How To)	Remove with petroleum products, mineral spirits, or contact cleaner.

Last revised: 11/28/2017
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.

CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.