

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### **0EC1 1/2" Oec CNDT Outlet Body & CVR** *Crouse-Hinds*

Catalog Number	0EC1
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Oe Conduit Outlet Body
	With Cover, Feraloy Iron Alloy, C Shape, 1/2"
Weight per unit	1.8 (lbs/each)
Product Category	Bodies & Covers

#### **Features**

Threaded connection dimensions 5.5000 IN X 1.8100 IN X 1.5600 IN

#### Material, Color, and Finish

Finish Electrogalvanized With Aluminum Acrylic Painted

#### **Dimensions and Weight**

1/2 in Hub Size

#### **Descriptions**

Description

Bosoniption	I/E OLOGINET COTELT BODT & OVIK
extra long description	CRS-H OEC1 1/2 CNDT OUTLET BODY CVR
Features	OE and EKC conduit bodies from Eaton's Crouse-Hinds Division are installed in conduit systems within hazardous areas to protect conductors in threaded rigid conduit, provide an opening in the conduit system for pulling or splicing conductors, interconnect lengths of conduit, change direction of conduit, and provide access for maintenance and future system changes. OE and EKC conduit bodies are certified for use in Class I, Division 1 and Class II, Division 1 hazardous areas.
Long Description	Eaton Crouse-Hinds series Condulet OE conduit outlet body with cover, Feraloy iron alloy, C shape, 1/2"
Product Type	1/2 CNDT Outlet Body CVR
Special Features	With Cover

1/2" OEC CNDT OUTLET BODY & CVR

#### **Manufacturer Information**

Brand	Crouse-Hinds
GTIN	00782274551807
Manufacturers Part Number	OEC1
UPC	782274551807

#### Taxonomies, Classifications, and Categories

Conduit outlet body with cover Type



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	2
Weight Per each	1.8
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 Group E F G, Class II Div 2
	Group F G, Class III
standard	UL 886, CSA C22.2