

## ELLIOTT ELECTRIC SUPPLY No Doliver Lower Cost. Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



**OEC2 3/4" Oec Cond Body & CVR** Crouse-Hinds

Catalog Number	0EC2
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Oe Conduit Outlet Body With Cover, Feraloy Iron Alloy, C Shape, 3/4"
Weight per unit	2.3 (lbs/each)
Product Category	Bodies & Covers
eatures	
connection	Threaded
dimensions	5.6900 IN X 2.0600 IN X 1.8800 IN
Naterial, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
imensions and Weight	
Hub Size	1 in
escriptions	
Description	3/4" OEC COND BODY & CVR
extra long description	CRS-H OEC2 3/4 CNDT OUTLET BODY CVR
Features	OE and EKC conduit bodies from Eaton's Crouse-Hinds Division are installed in conduit systems within hazardous areas to protect conductors in threaded rigid conduit, provide an opening in the conduit system for pulling or splicing conductors, interconnect lengths of conduit, change direction of conduit, and provide access for maintenance and future system changes. OE and EKC conduit bodies are certified for use in Class I, Division 1 and Class II, Division 1 hazardous areas.
Long Description	Eaton Crouse-Hinds series Condulet OE conduit outlet body with cover, Feraloy iron alloy, C shape, 3/4"
Product Type	3/4 CNDT Outlet Body CVR
Special Features	With Cover
Nanufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274551906
Manufacturers Part Number	OEC2
UPC	782274551906
axonomies, Classifications, and (	•
	HAZARDOUS LOCATION FITTINGS
Туре	Conduit outlet body with cover



## **E**LLIOTT **E**LECTRIC **S**UPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Packaging

Carton	1
Package	2
Weight Per each	2.3

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 Group E F G, Class II Div 2
	Group F G, Class III
standard	UL 886, CSA C22.2