# GE ProLine® Incandescent Lamps

## Value Priced Lighting Products from a Trusted Source




**An exciting line of our most frequently used SKUs specially packed for:**

- Small Business Owners
- Contractors
- Building Management Personnel (Apartments / Motels / Malls)

**Retailer Benefits:**

- Multi-Pack is scannable
- Trilingual packaging educates users in applications
- Complements GE Brand Value Sell
- One source for all your lighting needs

**User Benefits:**

- Bulbs are individually sleeved - Eliminates breakage, no loose bulbs
- Quick / Easy / Convenient Shopping
- 130, 120 and 12 Volt Offerings

## GE ProLine® Incandescent Lamps

| Product Code | Description | Volts | Watts | Life | Initial Lumens | Pack Size | Base |
|---|---|---|---|---|---|---|---|
| Incandescent A15 | | | | | | | |
| 97861 | 40A15CL/PRO-130V | 130 | 40 | 1500 | 300 | 24 | Medium |
| | | Ratings @ 120 | 36 | 4000 | 215 | | |
| Incandescent A19 | | | | | | | |
| 72015 | 38A/IF-PROLINE | 130 | 38 | 2000 | 390 | 24 | Medium |
| | | Ratings @ 120 | 34 | 5400 | 290 | | |
| 72016 | 57A/IF-PROLINE | 130 | 57 | 1200 | | 24 | Medium |
| | | Ratings @ 120 | 50 | 3200 | 570 | | |
| 72017 | 71A/IF-PROLINE | 130 | 71 | 1000 | 1040 | 24 | Medium |
| | | Ratings @ 120 | 63 | 2600 | 780 | | |
| 72019 | 38A/CL-PROLINE | 130 | 38 | 1500 | 435 | 24 | Medium |
| | | Ratings @ 120 | 34 | 4000 | 310 | | |
| 72021 | 57A/CL-PROLINE | 130 | 57 | 1200 | 770 | 24 | Medium |
| | | Ratings @ 120 | 50 | 3200 | 575 | | |
| 72022 | 71A/CL-PROLINE | 130 | 71 | 1000 | 1050 | 24 | Medium |
| | | Ratings @ 120 | 63 | 2600 | 785 | | |
| 97485 | 60A/Y-PRO-24Pk Bug Light | 120 | 60 | 1500 | 550 | 24 | Medium |
| Incandescent G25 | | | | | | | |
| 24656 | 25G25/CL PROLINE | 130 | 25 | 1500 | 190 | 6 | Medium |
| | | Ratings @ 120 | 22 | 3900 | 140 | | |
| 24657 | 25G25/W PROLINE | 130 | 25 | 1500 | 170 | 6 | Medium |
| | | Ratings @ 120 | 22 | 3900 | 130 | | |
| 24658 | 40G25/CL PROLINE | 130 | 40 | 1500 | 370 | 6 | Medium |
| | | Ratings @ 120 | 35 | 3900 | 280 | | |
| 24660 | 40G25/W PROLINE | 130 | 40 | 1500 | 340 | 6 | Medium |
| | | Ratings @ 120 | 35 | 3900 | 260 | | |
| 24662 | 60G25/CL PROLINE | 130 | 60 | 1500 | 670 | 6 | Medium |
| | | Ratings @ 120 | 53 | 3900 | 505 | | |
| 24664 | 60G25/W PROLINE | 130 | 60 | 1500 | 620 | 6 | Medium |
| | | Ratings @ 120 | 53 | 3900 | 470 | | |
| Incandescent BC/CAC | | | | | | | |
| 24778 | 40BC/CL/PRO-12PK | 130 | 40 | 1500 | 370 | 12 | Cand Screw |
| 24779 | 60BC/CL/PRO-12PK | 130 | 60 | 1500 | 650 | 12 | Cand Screw |
| 24782 | 40CAC/PRO-12PK | 130 | 40 | 1500 | 370 | 12 | Cand Screw |
| Incandescent T6 | | | | | | | |
| 24992 | 25T6.5/CL/PRO | 130 | 25 | 1000 | 200 | 24 | Intermediate |
| 24993 | 15T6/CL/PRO | 145 | 15 | 2000 | 100 | 24 | Cand Screw |
| Incandescent Reflector | | | | | | | |
| 73030 | 45R20/130V-PRO | 130 | 45 | 2000 | 300 | 6 | Medium |
| | | Ratings @ 120 | 40 | 4000 | 230 | | |
| 24705 | 65BR30/PROLINE | 130 | 65 | 2000 | 470 | 6 | Medium |
| | | Ratings @ 120 | 58 | 5200 | 360 | | |
| 24998 | 65BR40/FL/PRO | 130 | 65 | 2000 | 475 | 6 | Medium |
| | | Ratings @ 120 | 57 | 4000 | 360 | | |
| 24986 | 250R40/1/PRO Heat Lamp | 120 | 220 | 14000 | -- | 12 | Medium |
| 73027 | 45R20/YR-PRO | 120 | 45 | 1500 | 350 | 6 | Medium |
| 75211 | 65BR30FL/YR-PRO | 120 | 65 | 1500 | 640 | 6 | Medium |
| 75212 | 65BR40FL/YR-PRO | 120 | 65 | 1500 | 635 | 6 | Medium |

These highlighted products will be delisted on 1/1/14 as a result of legislation.

These highlighted products were delisted on 1/1/13 as a result of legislation.

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions.

imagination at work

For additional product and application information, please consult GE's Website: www.gelighting.com

65392 8/2013 Printed in USA © GE 2013

# GE ProLine®
# PAR Halogen Lamps

| Product Code | Description | Volts | Watts | Life | Initial Lumens | Pack Size | Base |
|---|---|---|---|---|---|---|---|
| **Halogen PAR20** | | | | | | | |
| 90607 | 50PAR20/SP10/PRO | 130 | 50 | 2000 | 540 | 6 | Medium |
| 90608 | 50PAR20/FL25/PRO | Rating @ 120 | 44 | 4000 | 410 | | |
| | | 130 | 50 | 2000 | 540 | 6 | Medium |
| | | Rating @ 120 | 44 | 4000 | 410 | | |
| 75213 | 50PAR20/FL25/PRO120 | 120 | 50 | 1500 | 550 | 6 | Medium |
| 62231 | 75PARHIR+XL/8K/FL25T | 120 | 50 | 1500 | 550 | 6 | Medium |
| **Halogen PAR30** | | | | | | | |
| 90609 | 50PAR30/SP10/PRO | 130 | 50 | 2000 | 540 | 6 | Medium |
| | | Rating @ 120 | 44 | 4000 | 410 | | |
| 90610 | 50PAR20/FL25/PRO | 130 | 50 | 2000 | 540 | 6 | Medium |
| | | Rating @ 120 | 44 | 4000 | 410 | | |
| 75219 | 75PAR30LN/FL25/PRO/120 | 120 | 75 | 1500 | 960 | 6 | Medium |
| 75220 | 75PAR30LN/SP10/PRO/120 | 120 | 75 | 1500 | 960 | 6 | Medium |
| **Halogen PAR30 Long Neck** | | | | | | | |
| 86910 | 75PAR30LN/SP10/PRO | 130 | 75 | 2000 | 940 | 6 | Medium |
| | | Rating @ 120 | 66 | 4000 | 714 | | |
| 86911 | 75PAR30LN/FL25/PRO | 130 | 75 | 2000 | 940 | 6 | Medium |
| | | Rating @ 120 | 66 | 4000 | 714 | | |
| 75214 | 75PAR30LN/FL25/PRO/120 | 120 | 75 | 1500 | 940 | 6 | Medium |
| 75218 | 75PAR30LN/SP10/PRO/120 | 120 | 75 | 1500 | 940 | 6 | Medium |
| **Halogen PAR38** | | | | | | | |
| 75732 | 50PAR/H/FL25/PRO/120 | 120 | 50 | 1500 | 525 | 6 | R7S |
| 75733 | 75PAR/H/FL25/PRO/120 | 120 | 75 | 1500 | 940 | 6 | R7S |
| 75215 | 90PAR/H/FL25/PRO/120 | 120 | 90 | 1500 | 1260 | 6 | R7S |
| 75216 | 120PAR/H/FL25/PRO/120 | 120 | 120 | 1500 | 1740 | 6 | R7S |
| 81588 | 75PAR/H/FL25/PRO | 130 | 75 | 2500 | 1050 | 6 | Medium |
| | | Rating @ 120 | 66 | 5000 | 800 | | |
| 81589 | 90PAR/H/FL25/PRO | 130 | 90 | 2500 | 1310 | 6 | Medium |
| | | Rating @ 120 | 79 | 5000 | 1000 | | |
| 24865 | 100PAR/H/FL25/PRO | 130 | 100 | 2000 | 1500 | 6 | Medium |
| | | Rating @ 120 | 88 | 4000 | 1150 | 6 | Medium |

These highlighted products were delisted on 7/14/12 as a result of legislation.

imagination at work

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions.

For additional product and application information, please consult GE's Website: www.gelighting.com

65392 8/2013 Printed in USA © GE 2013

# GE ProLine®
# Halogen Lamps




| Product Code | Description | Volts | Watts | Life | Initial Lumens | Pack Size | Base |
|---|---|---|---|---|---|---|---|
| **Halogen T4** | | | | | | | |
| 24881 | Q100CL/MC/PROLINE | 120 | 100 | 2000 | 1600 | 6 | Mini-can |
| **Halogen SEQ** | | | | | | | |
| 24924 | Q10T3/12V/CL/PRO | 12 | 10 | 2000 | 140 | 6 | 2 pin G4 |
| 24925 | Q20T3/12V/CL/PRO | 12 | 20 | 2000 | 350 | 6 | 2 pin G4 |
| 24926 | Q50T3/12V/CL/PRO | 12 | 50 | 2000 | 850 | 6 | 2 pin GY6.35 |
| **Halogen DEQ** | | | | | | | |
| 24927 | Q100T3CL/PRO-6PK | 120 | 100 | 1500 | 1650 | 6 | R7S |
| 24928 | Q300T2.5/CL/PRO | 120 | 300 | 2000 | 5950 | 6 | R7S |
| 24929 | Q300T3CL/PRO-6PK | 130 | 300 | 2000 | 5760 | 6 | R7S |
| 24930 | Q500T2.5/CL/PRO | 120 | 500 | 2000 | 10550 | 6 | R7S |
| 24931 | Q500T3CL/PRO-6PK | 130 | 500 | 2000 | 10300 | 6 | R7S |
| 24932 | Q1500T3CL/PRO-6PK | 240 | 1500 | 2000 | 35800 | 6 | R7S |
| **Halogen MR16 with Cover Glass** | | | | | | | |
| 85991 | Q20MR16/FL/PRO/CG | 12 | 20 | 2000 | | 10 | GU5.3 |
| 85992 | Q20MR16/SP/PRO/CG | 12 | 20 | 2000 | | 10 | GU5.3 |
| 85993 | Q50MR16/FL/PRO/CG | 12 | 50 | 2000 | | 10 | GU5.3 |
| 85994 | Q50MR16/SP/PRO/CG | 12 | 50 | 2000 | | 10 | GU5.3 |
| **Halogen MR16 with Cover Glass** | | | | | | | |
| 75635 | Q20MR16FL/PRO-25 | 12 | 20 | 2500 | | 10 | GU5.3 |
| 75636 | Q20MR16SP/PRO-25 | 12 | 20 | 2500 | | 10 | GU5.3 |
| 75637 | Q50MR16FL/PRO-25 | 12 | 50 | 2500 | | 10 | GU5.3 |
| 75638 | Q50MR16SP/PRO-25 | 12 | 50 | 2500 | | 10 | GU5.3 |
| **Halogen MR16 Open** | | | | | | | |
| 75734 | Q20MR16FLNCG-PRO | 12 | 20 | 2000 | | 10 | GX5.3 |
| 75738 | Q50MR16FLNCG-PRO | 12 | 50 | 2000 | | 10 | GX5.3 |
| 75741 | Q50MR16SPNCG-PRO | 12 | 50 | 2000 | | 10 | GX5.3 |

# GE ProLine®
# Linear Fluorescent T5/T8

| Product Code | Description | Shape | Base | Watts | Nominal Length (In) | Case Quantity | Rated Life (3 Hour/Start) | Initial Lumens | Color Temp. K |
|---|---|---|---|---|---|---|---|---|---|
| **Linear Fluorescent – T8** | | | | | | | | | |
| 63542 | F32T8/730/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2450 | 3000 |
| 63543 | F32T8/735/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2450 | 3500 |
| 63544 | F32T8/741/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2450 | 4100 |
| 63545 | F32T8/750/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2450 | 5000 |
| 63546 | F32T8/830/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2925 | 3000 |
| 63547 | F32T8/835/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2925 | 3500 |
| 63548 | F32T8/841/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2925 | 4100 |
| 63549 | F32T8/850/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2900 | 5000 |
| **Linear Fluorescent – T5** | | | | | | | | | |
| 61360 | F54T5/835ECO/PRO | T5 | Miniature Bipin (G5) | 54 | 45.2 | 40 | 17000 | 5000 | 3500 |
| 61361 | F54T5/841ECO/PRO | T5 | Miniature Bipin (G5) | 54 | 45.2 | 40 | 17000 | 5000 | 4100 |
| 61362 | F54T5/850ECO/PRO | T5 | Miniature Bipin (G5) | 54 | 45.2 | 40 | 17000 | 5000 | 5000 |

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions.

imagination at work

For additional product and application information, please consult GE's Website: www.gelighting.com

65392 8/2013 Printed in USA © GE 2013

# GE ProLine® Incandescent Lamps

## Value Priced Lighting Products from a Trusted Source




**An exciting line of our most frequently used SKUs specially packed for:**

- Small Business Owners
- Contractors
- Building Management Personnel (Apartments / Motels / Malls)

**Retailer Benefits:**

- Multi-Pack is scannable
- Trilingual packaging educates users in applications
- Complements GE Brand Value Sell
- One source for all your lighting needs

**User Benefits:**

- Bulbs are individually sleeved - Eliminates breakage, no loose bulbs
- Quick / Easy / Convenient Shopping
- 130, 120 and 12 Volt Offerings

## GE ProLine® Incandescent Lamps

| Product Code | Description | Volts | Watts | Life | Initial Lumens | Pack Size | Base |
|---|---|---|---|---|---|---|---|
| Incandescent A15 | | | | | | | |
| 97861 | 40A15CL/PRO-130V | 130 | 40 | 1500 | 300 | 24 | Medium |
| | | Ratings @ 120 | 36 | 4000 | 215 | | |
| Incandescent A19 | | | | | | | |
| 72015 | 38A/IF-PROLINE | 130 | 38 | 2000 | 390 | 24 | Medium |
| | | Ratings @ 120 | 34 | 5400 | 290 | | |
| 72016 | 57A/IF-PROLINE | 130 | 57 | 1200 | | 24 | Medium |
| | | Ratings @ 120 | 50 | 3200 | 570 | | |
| 72017 | 71A/IF-PROLINE | 130 | 71 | 1000 | 1040 | 24 | Medium |
| | | Ratings @ 120 | 63 | 2600 | 780 | | |
| 72019 | 38A/CL-PROLINE | 130 | 38 | 1500 | 435 | 24 | Medium |
| | | Ratings @ 120 | 34 | 4000 | 310 | | |
| 72021 | 57A/CL-PROLINE | 130 | 57 | 1200 | 770 | 24 | Medium |
| | | Ratings @ 120 | 50 | 3200 | 575 | | |
| 72022 | 71A/CL-PROLINE | 130 | 71 | 1000 | 1050 | 24 | Medium |
| | | Ratings @ 120 | 63 | 2600 | 785 | | |
| 97485 | 60A/Y-PRO-24Pk Bug Light | 120 | 60 | 1500 | 550 | 24 | Medium |
| Incandescent G25 | | | | | | | |
| 24656 | 25G25/CL PROLINE | 130 | 25 | 1500 | 190 | 6 | Medium |
| | | Ratings @ 120 | 22 | 3900 | 140 | | |
| 24657 | 25G25/W PROLINE | 130 | 25 | 1500 | 170 | 6 | Medium |
| | | Ratings @ 120 | 22 | 3900 | 130 | | |
| 24658 | 40G25/CL PROLINE | 130 | 40 | 1500 | 370 | 6 | Medium |
| | | Ratings @ 120 | 35 | 3900 | 280 | | |
| 24660 | 40G25/W PROLINE | 130 | 40 | 1500 | 340 | 6 | Medium |
| | | Ratings @ 120 | 35 | 3900 | 260 | | |
| 24662 | 60G25/CL PROLINE | 130 | 60 | 1500 | 670 | 6 | Medium |
| | | Ratings @ 120 | 53 | 3900 | 505 | | |
| 24664 | 60G25/W PROLINE | 130 | 60 | 1500 | 620 | 6 | Medium |
| | | Ratings @ 120 | 53 | 3900 | 470 | | |
| Incandescent BC/CAC | | | | | | | |
| 24778 | 40BC/CL/PRO-12PK | 130 | 40 | 1500 | 370 | 12 | Cand Screw |
| 24779 | 60BC/CL/PRO-12PK | 130 | 60 | 1500 | 650 | 12 | Cand Screw |
| 24782 | 40CAC/PRO-12PK | 130 | 40 | 1500 | 370 | 12 | Cand Screw |
| Incandescent T6 | | | | | | | |
| 24992 | 25T6.5/CL/PRO | 130 | 25 | 1000 | 200 | 24 | Intermediate |
| 24993 | 15T6/CL/PRO | 145 | 15 | 2000 | 100 | 24 | Cand Screw |
| Incandescent Reflector | | | | | | | |
| 73030 | 45R20/130V-PRO | 130 | 45 | 2000 | 300 | 6 | Medium |
| | | Ratings @ 120 | 40 | 4000 | 230 | | |
| 24705 | 65BR30/PROLINE | 130 | 65 | 2000 | 470 | 6 | Medium |
| | | Ratings @ 120 | 58 | 5200 | 360 | | |
| 24998 | 65BR40/FL/PRO | 130 | 65 | 2000 | 475 | 6 | Medium |
| | | Ratings @ 120 | 57 | 4000 | 360 | | |
| 24986 | 250R40/1/PRO Heat Lamp | 120 | 220 | 14000 | -- | 12 | Medium |
| 73027 | 45R20/YR-PRO | 120 | 45 | 1500 | 350 | 6 | Medium |
| 75211 | 65BR30FL/YR-PRO | 120 | 65 | 1500 | 640 | 6 | Medium |
| 75212 | 65BR40FL/YR-PRO | 120 | 65 | 1500 | 635 | 6 | Medium |

These highlighted products will be delisted on 1/1/14 as a result of legislation.

These highlighted products were delisted on 1/1/13 as a result of legislation.

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions.

imagination at work

For additional product and application information, please consult GE's Website: www.gelighting.com

65392 8/2013 Printed in USA © GE 2013

# GE ProLine®
# PAR Halogen Lamps

| Product Code | Description | Volts | Watts | Life | Initial Lumens | Pack Size | Base |
|---|---|---|---|---|---|---|---|
| **Halogen PAR20** | | | | | | | |
| 90607 | 50PAR20/SP10/PRO | 130 | 50 | 2000 | 540 | 6 | Medium |
| 90608 | 50PAR20/FL25/PRO | Rating @ 120 | 44 | 4000 | 410 | | |
| | | 130 | 50 | 2000 | 540 | 6 | Medium |
| | | Rating @ 120 | 44 | 4000 | 410 | | |
| 75213 | 50PAR20/FL25/PRO120 | 120 | 50 | 1500 | 550 | 6 | Medium |
| 62231 | 75PARHIR+XL/8K/FL25T | 120 | 50 | 1500 | 550 | 6 | Medium |
| **Halogen PAR30** | | | | | | | |
| 90609 | 50PAR30/SP10/PRO | 130 | 50 | 2000 | 540 | 6 | Medium |
| | | Rating @ 120 | 44 | 4000 | 410 | | |
| 90610 | 50PAR20/FL25/PRO | 130 | 50 | 2000 | 540 | 6 | Medium |
| | | Rating @ 120 | 44 | 4000 | 410 | | |
| 75219 | 75PAR30LN/FL25/PRO/120 | 120 | 75 | 1500 | 960 | 6 | Medium |
| 75220 | 75PAR30LN/SP10/PRO/120 | 120 | 75 | 1500 | 960 | 6 | Medium |
| **Halogen PAR30 Long Neck** | | | | | | | |
| 86910 | 75PAR30LN/SP10/PRO | 130 | 75 | 2000 | 940 | 6 | Medium |
| | | Rating @ 120 | 66 | 4000 | 714 | | |
| 86911 | 75PAR30LN/FL25/PRO | 130 | 75 | 2000 | 940 | 6 | Medium |
| | | Rating @ 120 | 66 | 4000 | 714 | | |
| 75214 | 75PAR30LN/FL25/PRO/120 | 120 | 75 | 1500 | 940 | 6 | Medium |
| 75218 | 75PAR30LN/SP10/PRO/120 | 120 | 75 | 1500 | 940 | 6 | Medium |
| **Halogen PAR38** | | | | | | | |
| 75732 | 50PAR/H/FL25/PRO/120 | 120 | 50 | 1500 | 525 | 6 | R7S |
| 75733 | 75PAR/H/FL25/PRO/120 | 120 | 75 | 1500 | 940 | 6 | R7S |
| 75215 | 90PAR/H/FL25/PRO/120 | 120 | 90 | 1500 | 1260 | 6 | R7S |
| 75216 | 120PAR/H/FL25/PRO/120 | 120 | 120 | 1500 | 1740 | 6 | R7S |
| 81588 | 75PAR/H/FL25/PRO | 130 | 75 | 2500 | 1050 | 6 | Medium |
| | | Rating @ 120 | 66 | 5000 | 800 | | |
| 81589 | 90PAR/H/FL25/PRO | 130 | 90 | 2500 | 1310 | 6 | Medium |
| | | Rating @ 120 | 79 | 5000 | 1000 | | |
| 24865 | 100PAR/H/FL25/PRO | 130 | 100 | 2000 | 1500 | 6 | Medium |
| | | Rating @ 120 | 88 | 4000 | 1150 | 6 | Medium |

These highlighted products were delisted on 7/14/12 as a result of legislation.

imagination at work

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions.

For additional product and application information, please consult GE's Website: www.gelighting.com

65392 8/2013 Printed in USA © GE 2013

# GE ProLine®
# Halogen Lamps




| Product Code | Description | Volts | Watts | Life | Initial Lumens | Pack Size | Base |
|---|---|---|---|---|---|---|---|
| **Halogen T4** | | | | | | | |
| 24881 | Q100CL/MC/PROLINE | 120 | 100 | 2000 | 1600 | 6 | Mini-can |
| **Halogen SEQ** | | | | | | | |
| 24924 | Q10T3/12V/CL/PRO | 12 | 10 | 2000 | 140 | 6 | 2 pin G4 |
| 24925 | Q20T3/12V/CL/PRO | 12 | 20 | 2000 | 350 | 6 | 2 pin G4 |
| 24926 | Q50T3/12V/CL/PRO | 12 | 50 | 2000 | 850 | 6 | 2 pin GY6.35 |
| **Halogen DEQ** | | | | | | | |
| 24927 | Q100T3CL/PRO-6PK | 120 | 100 | 1500 | 1650 | 6 | R7S |
| 24928 | Q300T2.5/CL/PRO | 120 | 300 | 2000 | 5950 | 6 | R7S |
| 24929 | Q300T3CL/PRO-6PK | 130 | 300 | 2000 | 5760 | 6 | R7S |
| 24930 | Q500T2.5/CL/PRO | 120 | 500 | 2000 | 10550 | 6 | R7S |
| 24931 | Q500T3CL/PRO-6PK | 130 | 500 | 2000 | 10300 | 6 | R7S |
| 24932 | Q1500T3CL/PRO-6PK | 240 | 1500 | 2000 | 35800 | 6 | R7S |
| **Halogen MR16 with Cover Glass** | | | | | | | |
| 85991 | Q20MR16/FL/PRO/CG | 12 | 20 | 2000 | | 10 | GU5.3 |
| 85992 | Q20MR16/SP/PRO/CG | 12 | 20 | 2000 | | 10 | GU5.3 |
| 85993 | Q50MR16/FL/PRO/CG | 12 | 50 | 2000 | | 10 | GU5.3 |
| 85994 | Q50MR16/SP/PRO/CG | 12 | 50 | 2000 | | 10 | GU5.3 |
| **Halogen MR16 with Cover Glass** | | | | | | | |
| 75635 | Q20MR16FL/PRO-25 | 12 | 20 | 2500 | | 10 | GU5.3 |
| 75636 | Q20MR16SP/PRO-25 | 12 | 20 | 2500 | | 10 | GU5.3 |
| 75637 | Q50MR16FL/PRO-25 | 12 | 50 | 2500 | | 10 | GU5.3 |
| 75638 | Q50MR16SP/PRO-25 | 12 | 50 | 2500 | | 10 | GU5.3 |
| **Halogen MR16 Open** | | | | | | | |
| 75734 | Q20MR16FLNCG-PRO | 12 | 20 | 2000 | | 10 | GX5.3 |
| 75738 | Q50MR16FLNCG-PRO | 12 | 50 | 2000 | | 10 | GX5.3 |
| 75741 | Q50MR16SPNCG-PRO | 12 | 50 | 2000 | | 10 | GX5.3 |

# GE ProLine®
# Linear Fluorescent T5/T8

| Product Code | Description | Shape | Base | Watts | Nominal Length (In) | Case Quantity | Rated Life (3 Hour/Start) | Initial Lumens | Color Temp. K |
|---|---|---|---|---|---|---|---|---|---|
| **Linear Fluorescent – T8** | | | | | | | | | |
| 63542 | F32T8/730/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2450 | 3000 |
| 63543 | F32T8/735/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2450 | 3500 |
| 63544 | F32T8/741/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2450 | 4100 |
| 63545 | F32T8/750/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2450 | 5000 |
| 63546 | F32T8/830/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2925 | 3000 |
| 63547 | F32T8/835/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2925 | 3500 |
| 63548 | F32T8/841/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2925 | 4100 |
| 63549 | F32T8/850/PRO/EC | T8 | Medium Bipin (G13) | 32 | 48.0 | 36 | 20000 | 2900 | 5000 |
| **Linear Fluorescent – T5** | | | | | | | | | |
| 61360 | F54T5/835ECO/PRO | T5 | Miniature Bipin (G5) | 54 | 45.2 | 40 | 17000 | 5000 | 3500 |
| 61361 | F54T5/841ECO/PRO | T5 | Miniature Bipin (G5) | 54 | 45.2 | 40 | 17000 | 5000 | 4100 |
| 61362 | F54T5/850ECO/PRO | T5 | Miniature Bipin (G5) | 54 | 45.2 | 40 | 17000 | 5000 | 5000 |

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions.

imagination at work

For additional product and application information, please consult GE's Website: www.gelighting.com

65392 8/2013 Printed in USA © GE 2013