


# ELLIOTT ELECTRIC SUPPLY 700 Industry Way Suite 10 75078-0000, TX Prosper Phone: 469-899-3981

We Deliver...Lower Cost, Quality Products, & Personal Service





#### 280DCX 3/8 MC FMC to 1/2" Emt

Nsi Industries

Nsi Industries	
Emt to Ac/MC/FMC/NM Transition Fitting	
0.0700 (lbs/each)	
Die Cast Set Screw Emt to Flex	
0.615	

## **Dimensions and Weight**

Length 1.51

# **Descriptions**

Description	3/8 MC FMC TO 1/2" EMT
extra long description	BPT 280-DCX 3/8 MC FMC to 1/2" EMT
Long Description	EMT to AC/MC/FMC/NM Transition Fitting
Product Type	3/8 MC FMC to 1/2" Emt
Special Features	For dry locations only. Max wire fill is 60% or 0.137 sq. inches.

#### **Manufacturer Information**

Brand	Nsi Industries
GTIN	00781747092793
Manufacturers Part Number	280-DCX
UPC	781747092793

#### Taxonomies, Classifications, and Categories

Category Description	DIECAST EMT FITTINGS	
Туре	COUPLING	
Trade Size		

Trade Size 0.5

# **Packaging**

onagg		
Carton	25	
Package		
Weight Per each		

700 Industry Way Suite 10 75078-0000, TX Prosper Phone: 469-899-3981

Fax: 469-899-3982

#### Uses, Certifications, and Standards

Application

Transition fitting for use between 1/2" EMT to 3/8" Steel and Aluminum FMC, metal clad and armored cable assemblies with O.D. of .43-.61 (14/2 to 10/3 within the specified ranges), as well as 14/2 to 10/3 NM Cables, (2) 14/2 or (2) 12/2 NM Cables stacked, or the following combinations: 14/2 & 12/2, 14/2 & 12/3, 14/3 & 12/2. AC/MC should be prepared to the desired length and fed through the fitting. AC/MC/MCIA and FMC should be inserted until the armor engages with the endstop at the center of the fitting.

standard

UL