

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



301163 Weatherproof Wire Conn, 63 Gray/DK Blue, 15/Card

Catalog Number	301163
Manufacturer	Ideal
Description	MDL 63 Gray-Blue 15 Clam
Weight per unit	0.0179 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out
atures	
Quantity	Card of 15
aterial, Color, and Finish	
Color	Gray
escriptions	
Description	WEATHERPROOF WIRE CONN, 63 GRAY/DK BLUE, 15/CARD
extra long description	IDEAL 30-1163 MDL 63 GRAY-BLUE 15 C
Features	100% Silicone-based sealant protects against moisture and
	corrosionUL Listed to 486G Sealed Twist-On Wire Connector for
	use in damp/wet locations or above-grade applicationsEasy to
	apply, pre-filled twist-on wire connectorsSwept wing design is
	built for comfort and efficiencyEliminates the need for
	heat-shrink or excessive tapingTough, UL 94V-2 flame-retardant
	shell rated at 105°C (221°F)Models 61 and 63 approved for
	bonding and grounding applicationsFor use in damp/wet locatio
Lang Description	or above-grade applications
Long Description	MDL 63 GRAY-BLUE 15 CLAM
Product Type Special Features	MDL 63 Gray-Blue 15 Clam Silicone-based sealant protects against moisture and corrosion.
special reatures	Easy to apply pre-filled twist-on wire connectors
anufacturer Information	Lasy to apply pro filled twist of twile confidences
Brand	Ideal
GTIN	00783250758166
Manufacturers Part Number	30-1163
sub brand	WeatherProof ®
UPC	783250758166

Taxo

Category Description	Datacom Wiring Devices and Accessories
Туре	Model 63® Connector
Availability	

Availability

minimum qty 15



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

a				

Carton	15	
Package	75	
Weight Per each	0.0179	

Uses, Certifications, and Standards

,	
Application	Handles wire sizes from #16 to #6 AWG copper. Minimum of 3
	#14 AWG. Maximum of 2 #8 & 1 #10 AWG.
standard	UL listed for 486D for use in damp/wet locations
Temperature Rating	105