

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

30273 Wire-Nut Wire Conn, Model 73B Orange, 500/Bag		
Catalog Number	30273	
Catalog Number Manufacturer	Ideal	
Description	Twist-On Wire Connector, Orange Insulation Color, 1 to 5 Conductors, 600 V Ac, 1.35 LB	
Weight per unit	1.4 (lbs/each)	
Product Category	Electrical Fixture Conn (Nuts	
Features		
Material	Flame-Retardant Polypropylene	
Number of Conductors	1 to 5	
Voltage Rating	600	
Material, Color, and Finish		
Color	Orange	
Descriptions		
Description	WIRE-NUT WIRE CONN, MODEL 73B ORANGE, 500/BAG	
extra long description	IDEAL 30-273 WIRENUT 73B ORANGE, 50	
Features	The IDEAL Wire-Nut Wire Connector set new standards for innovation, quality and convenience when it was first introduced in 1928. As the first screw-on wire connector in America, it literally set the industry standard for years to come.With a fixed, square-wire spring and a positive grip shell, the Wire-Nut is perfect to twist-on with fingers for a secure connection that will last. The refined wire range makes it the best choice for fine stranded wire applications. The Wire-Nut also features a tough, flame	
Manufacturer Information		
Brand	Ideal	
GTIN	00783250302734	
UPC	783250302734	
Taxonomies, Classifications, and	Categories	
Category Description	Detecom Wiring Devices and Accessories	
Туре	Twist-On	
Availability		
minimum qty	500	



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Packaging

Carton	500	
Package	5000	
Weight Per each	1.35	

## Uses, Certifications, and Standards

Application	Insulating or Joining 2 or more conductors
environmental conditions	Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 DEG F)
standard	CSA Certified to C22.2 #188, UL Listed to 486C, complies with
	Federal Specification W-S-610E