

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



35412 Wrench, Combo Ratcheting 5/16" *Greenlee Textron*

Catalog Number	35412
Manufacturer	Greenlee Textron
Description	Combination Ratcheting Wrench, 5/16". Compact Reversible
	Switch Allows A 15° Offset Of The Box End For Clearance Of
	Obstacles. 5° Ratcheting Design For Versatility and Ease Of Use In
	Tight Spaces. Polished Chrome Finish For Superior Corrosion
	Resistance. Precision Heads For Accurate Fastener Fit. Hardened
	For Durability and Longer Life. Exceeds Asme/Ansi Specifications.
	Lifetime Limited Warranty. Note: This Is Not An Insulated Tool.
Weight per unit	0.1050 (lbs/each)
Product Category	Pliers, Wrenches, Saw, Pouches

Features

Drive Size 5/16 in

Material, Color, and Finish

Finish POLISHED CHROME

Dimensions and Weight

Overall Length 5-5/16 IN (13.500 CM)

Descriptions

Description	WRENCH,COMBO RATCHETING 5/16"
extra long description	GRN 0354-12 WRENCH,COMBO RATCHETING
Long Description	Combination Ratcheting Wrench, 5/16". Compact reversible switch allows a 15° offset of the box end for clearance of obstacles. 5° ratcheting design for versatility and ease of use in tight spaces. Polished chrome finish for superior corrosion resistance. Precision heads for accurate fastener fit. Hardened for durability and longer life. Exceeds ASME/ANSI specifications. Lifetime limited warranty. Note: This is not an insulated tool.
Product Type	Wrench, Combo Ratcheting 5/16"

Manufacturer Information

Brand	GREENLEE
GTIN	00783310554950
Manufacturers Part Number	0354-12
UPC	783310554950

Taxonomies, Classifications, and Categories

Category Description	HAND TOOLS
Туре	Standard, Combination



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight	0.080 LB (0.080 KG)
Weight Per each	0.105
Uses, Certifications, and Stand	ards
Application	For Versatility And Ease Of Use In Tight Spaces And Accurate
	Fastener Fit
standard	ASME/ANSI