


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Type

35417 Wrench, Combo Ratcheting 5/8" *Greenlee Textron*

Soon	
Catalog Number	35417
Manufacturer	Greenlee Textron
Description	Combination Ratcheting Wrench, 5/8". Compact Reversible Switch Allows A 15° Offset Of The Box End For Clearance Of Obstacles. 5° Ratcheting Design For Versatility and Ease Of Use In
	Tight Spaces. Polished Chrome Finish For Superior Corrosion Resistance. Precision Heads For Accurate Fastener Fit. Hardened For Durability and Longer Life. Exceeds Asme/Ansi Specifications Lifetime Limited Warranty. Note: This Is Not An Insulated Tool.
Weight per unit	0.3900 (lbs/each)
Product Category	Pliers, Wrenches, Saw, Pouches
Features	
Drive Size	5/8 IN
Material, Color, and Finish	
Finish	POLISHED CHROME
Dimensions and Weight	
Overall Length	8-3/8 IN (21.600 CM)
Descriptions	
Description	WRENCH,COMBO RATCHETING 5/8"
extra long description	GRN 0354-17 WRENCH,COMBO RATCHETING
Long Description	Combination Ratcheting Wrench, 5/8". Compact reversible
	switch allows a 15° offset of the box end for clearance of
	obstacles. 5° ratcheting design for versatility and ease of use in
	tight spaces. Polished chrome finish for superior corrosion
	resistance. Precision heads for accurate fastener fit. Hardened
	for durability and longer life. Exceeds ASME/ANSI specifications.
Product Type	Lifetime limited warranty. Note: This is not an insulated tool. Wrench, Combo Ratcheting 5/8"
Manufacturer Information	
Brand	GREENLEE
GTIN	00783310555001
Manufacturers Part Number	0354-17
UPC	783310555001
Taxonomies, Classifications, and Category Description	· = == =
_	

Standard, Combination



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight	0.370 LB (0.170 KG)
Weight Per each	0.39
Uses, Certifications, and Standards	
Application	For Versatility And Ease Of Use In Tight Spaces And Accurate
	Fastener Fit

ASME/ANSI