

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Category Description

Type

35BL12 Vinyl Color Coding Elec Tape 35, 1/2" X 20', BL

Catalog Number	35BL12
Manufacturer	Minnesota Mining (3M)
Description	Scotch® Vinyl Color Coding Electrical Tape 35 Is A 7 Mil Thick, Premium Grade, Color Coded Electrical Tape. This Flame Retardant Tape Is Suitable For Use In Phase Identification, Color Coding Of Motor Leads and Piping Systems and For Marking Safety Areas. This Tape Is 600V Rated and Withstands A Temperature Range Of 32 to 221 °F (0 to 105 °C).
Weight per unit	0.0052 (lbs/each)
Product Category	Markers & Marking Tapes - Tape
criptions	
Description extra long description	VINYL COLOR CODING ELEC TAPE 35, 1/2" X 20', BL 3M 7000132637 Scotch® Multi-Colored
Features	For purposes of color-coding, phasing and insulating power systems, you can trust Scotch® Vinyl Electrical Tape 35. Its strong rubber-resin adhesive and elastic PVC backing provide reliable durability in electrical and mechanical applications. This flame-retardant tape is tough against abrasion and moisture, and offers great resistance from contact with chemicals, solvents, acids and alkalis. Use it for insulating electrical wires and on synthetic cables, jackets and splicing compounds. This tape is VDE an
Long Description	Scotch® Vinyl Color Coding Electrical Tape 35 is a 7 mil thick, premium grade, color coded electrical tape. This flame retardant tape is suitable for use in phase identification, color coding of motor leads and piping systems and for marking safety areas. This tape is 600V rated and withstands a temperature range of 32 to 221 °F (0 to 105 °C).
Product Type	Scotch® Multi-Colored Vinyl Electrical Tape 35
Special Features	Color Coding
nufacturer Information Brand	Scotch
GTIN	00054007102403
Manufacturers Part Number	35-1/2X20FT-BL
sub brand	Scotch
UPC	054007102403

TAPE

VINYL



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	10
Weight Per each	0.0052
Uses, Certifications, and Standards	
Application	Premium
standard	UL Listed, CSA Certified, VDE 0340-TEIL1