

Catalog Number: PRHELB-3X90 UPC: 784011200443





Description

3X90 PVC Coated Standard Elbow

Factory-bent PVC coated elbows are more accurate, quicker to install and more economical because they eliminate field bending time and waste of material. Electrical continuity is maintained across assembled joints.

Application

- · Factory-bent for accurate, quicker to install and eliminates costly field bending and waste of
- · Factory-bent for accurate, quicker to install and eliminates costly field bending and waste of material

Features


- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 12 trade sizes from 1/2" through 6"
- Available in standard sizes 90°, 60°, 45°, 30° bends
- Color-coded thread protector caps for quick identification of conduit size

General

Material:	STEEL
Exterior Finish:	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish:	A nominal .002 inch (2 mil) red urethane
Thread Finish:	A red urethane coating over steel
Thread Protector Color:	Blue

Dimensions

Metric Size Designators	78
Nipple Length (Inches)	32
Diameter - External (Inches)	3.58
Diameter - Internal (Inches)	3.08
Radius A (Inches)	32
Radius B - Standard (Inches)	13
Radius C (Inches)	14.79
Offset D (Inches)	17
Offset E (Inches)	18.79
Offset F (Inches)	20.58
Tangent (Inches)	5.79





Catalog Number: PRHELB-3X90 UPC: 784011200443

CULUSTED



Technical / Specification Documents

Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
Installer Certification and Tools	AVAILABLE ON WEBSITE
Chemical Resistance Charts	AVAILABLE ON WEBSITE
Performance Specifications	AVAILABLE ON WEBSITE

Standards

UL 6:	E2314
CSA Certified:	C22.2 No. 45

Notes

Both PVC and zinc coatings have been investigated as primary protection against corrosion.

Restricted for use with threaded fittings only.



Catalog Number: PRHELB-3X90 UPC: 784011200443





Description

3X90 PVC Coated Standard Elbow

Factory-bent PVC coated elbows are more accurate, quicker to install and more economical because they eliminate field bending time and waste of material. Electrical continuity is maintained across assembled joints.

Application

- · Factory-bent for accurate, quicker to install and eliminates costly field bending and waste of
- · Factory-bent for accurate, quicker to install and eliminates costly field bending and waste of material

Features


- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 12 trade sizes from 1/2" through 6"
- Available in standard sizes 90°, 60°, 45°, 30° bends
- Color-coded thread protector caps for quick identification of conduit size

General

Material:	STEEL
Exterior Finish:	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish:	A nominal .002 inch (2 mil) red urethane
Thread Finish:	A red urethane coating over steel
Thread Protector Color:	Blue

Dimensions

Metric Size Designators	78
Nipple Length (Inches)	32
Diameter - External (Inches)	3.58
Diameter - Internal (Inches)	3.08
Radius A (Inches)	32
Radius B - Standard (Inches)	13
Radius C (Inches)	14.79
Offset D (Inches)	17
Offset E (Inches)	18.79
Offset F (Inches)	20.58
Tangent (Inches)	5.79





Catalog Number: PRHELB-3X90 UPC: 784011200443

CULUSTED



Technical / Specification Documents

Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
Installer Certification and Tools	AVAILABLE ON WEBSITE
Chemical Resistance Charts	AVAILABLE ON WEBSITE
Performance Specifications	AVAILABLE ON WEBSITE

Standards

UL 6:	E2314
CSA Certified:	C22.2 No. 45

Notes

Both PVC and zinc coatings have been investigated as primary protection against corrosion.

Restricted for use with threaded fittings only.