

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1220 Elm Street 75482-0000, TX Sulphur Springs Phone: 903-885-0024 Fax: 903-885-0352



## 71A8142001D 1-150W 480 HP Bal

Advance By Signify

Catalog Number	71A8142001D
Manufacturer	Advance By Signify
Description  Reliable Performance Vacuum-Pressure Impregnation Re-Enforce The Electrical Insulation Of The Ballast, Pre Moisture, Inhibit Noise, and Dissipate Heat; Pre-Insula Leads Reduce The Risk Of Shock and Shrink Installatio Basic Ballast Is The Open Core and Coil Which Is Most As A Component Within A Lighting Luminaire. The Coi Also Forms The Nucleus Of Philips Advance'S Five Oth Configurations. Vacuum-Pressure Impregnated With A Silica-Filled Pol	
Weight per unit	10.0 (lbs/each)
Product Category	Hid Ballast Kits
Features	
ANSI Code	S55
Ballast Factor	1
dimmable	No
Lamp Type	HPS
Number of Lamps	1
Power Factor	0.90
Power Rating	150
start type	Pulse
Voltage Rating	480
Wattage	150
<b>Dimensions and Weight</b>	
Height	1.69
Length	15.55
Width	1.1



# ELLIOTT ELECTRIC SUPPLY 1220 Elm Street 75482-0000, TX Sulphur Springs Phone: 903-885-0024 Fax: 903-885-0352

es		

1-150W 480 HP BAL
ADV 193383 HPS BAL 150W S55 480V KI
Reliable performance Vacuum-pressure impregnation is used to re-enforce the electrical insulation of the ballast, preclude moisture, inhibit noise, and dissipate heat; Pre-insulated voltage leads reduce the risk of shock and shrink installation time The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations. Vacuum-pressure impregnated with a silica-filled pol
HPS Bal 150W S55 480V Kit

#### **Manufacturer Information**

Brand	Signify Electronics	
GTIN	00781087814215	
Manufacturers Part Number	193383	
LIPC.	781087814215	

### Taxonomies, Classifications, and Categories

Category Description	HID BALLASTS	
Туре	Magnetic HID	

#### **Packaging**

J		
Carton	1	
Weight	9.98	
Weight Per each	9.98	
3		

#### Uses, Certifications, and Standards

Application	Lighting Luminaire Component
Frequency Rating	60
standard	ULR;CSA certificate;RoHS Compliant