

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



# APPC150A 1-1/2 Cond Body Appleton/Oz Gedney

Catalog Number	APPC150A
Manufacturer	Appleton/Oz Gedney
Description	Form 85 Unilets Type C Conduit Outlet Body, Hub Size: 1-1/2 In, Form: 85, Length: 8.56 In, Width: 2-1/2 In, Height: 2-3/4 In, Material: Pressure Cast Aluminum, Finish: Epoxy Powder Coat, Connection: Tapered Female Threaded, Standard: UI 514A, UI 514B, UI File Number E2527, Csa C22.2 No. 18.3, Csa 065183, Nema FB-1, For Use With Rigid Steel, Rigid Aluminum Conduit, Imc and Emt
Weight per unit	1.2 (lbs/each)
Product Category	Alum
Features	
connection	Tapered Female Threaded
Form	85
Material	Pressure Cast Aluminum
Material, Color, and Finish	
Finish	Epoxy Powder Coated
<b>Dimensions and Weight</b>	
Height	2.75
Hub Size	1.5
Length	8.56
Width	2.5



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

-				•	
. 1	es	^rı	nt		nc
	_				
_	-	<b>UI</b> I	$\sim$ $\iota$		

Description	1-1/2 COND BODY
extra long description	APP C150-A 1-1/2 FORM 85 UNILET
Long Description	Form 85 UNILETS Type C Conduit Outlet Body, Hub Size: 1-1/2 IN, Form: 85, Length: 8.56 IN, Width: 2-1/2 IN, Height: 2-3/4 IN, Material: Pressure Cast Aluminum, Finish: Epoxy Powder Coat, Connection: Tapered Female Threaded, Standard: UL 514A, UL 514B, UL File Number E2527, CSA C22.2 No. 18.3, CSA 065183, NEMA FB-1, For Use With Rigid Steel, Rigid Aluminum Conduit, IMC And EMT
Product Type	1-1/2 Form 85 Unilet
Special Features	Serve as pulling fittings; Make bends in conduit system; Provide openings for splicing; Connect and change direction of conduit runs; Allow connections for branch runs; Permit access to conductors for maintenance; Smooth, rounded integral bushings in hubs protect conductor insulation; Roomy interiors: more wiring space; Accurately tapped, tapered threads for tight, rigid joints and excellent ground continuity; Form 85 copper free aluminum Unilets are lightweight, self oxidizing, self-renewing and offer a h
nufacturer Information	

Brand	Appleton
GTIN	00781381165303
Manufacturers Part Number	C150-A
sub brand	UNILETS
UPC	781381165303

## **Taxonomies, Classifications, and Categories**

Category Description	Fuses & Fuse Accessories
Туре	Type C Conduit Outlet Body

## **Packaging**

Carton	1	
Package	10	
Weight Per each	1.15	

## Uses, Certifications, and Standards

Application	For Use With Rigid Steel, Rigid Aluminum Conduit, IMC And EMT
standard	UL 514A, UL 514B, UL File Number E2527, CSA C22.2 No. 18.3,
	CSA 065183, NEMA FB-1