

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## BG68 1-1/2" to 2" Body CVR&GSKT Crouse-Hinds

Catalog Number	BG68	
Manufacturer	Crouse-Hinds	
Description	Eaton Crouse-Hinds Series Condulet B Mogul Blank Cover,	
	Feraloy Iron Alloy, Round Neoprene Gasket, 1-1/2" or 2"	
Weight per unit	5.9 (lbs/each)	
Product Category	Bodies & Covers	

**Features** 

dimensions 3.5600 IN X 1.4600 IN X 12.1900 IN Material FERALOY IRON ALLOY

Material, Color, and Finish

Finish Electrogalvanized With Aluminum Acrylic Painted

Descriptions

Description Description	1-1/2" TO 2" BODY CVR&GSKT
extra long description	CRS-H BG68 1 1/2 OR 2 IRON MOGUL CV
Features	Crouse-Hinds series mogul bodies are installed in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion
Long Description	Eaton Crouse-Hinds series Condulet B mogul blank cover, Feraloy iron alloy, Round neoprene gasket, 1-1/2" or 2"
Product Type	1 1/2 or 2 Iron Mogul CVR/Gask
Special Features	Round neoprene gasket

#### **Manufacturer Information**

Brand	Eaton
GTIN	00782274101903
Manufacturers Part Number	BG68
UPC	782274101903

### **Taxonomies, Classifications, and Categories**

Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Туре	Mogul blank cover



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Package	2
Weight Per each	5.9
Uses, Certifications, and Standa	ards
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D