

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Packaging Carton

Package

Weight Per each

BR120 Type BR BRKR 20A/1 Pole 120/240V 10K

Catalog Number	BR120
Manufacturer	Eaton Corp
Description	Eaton BR Thermal Magnetic Circuit Breaker, Type BR 1-Inch Plug-On Circuit Breaker, 20 A, 10 Kaic, Single-Pole, 120/240V, BR #14-4 Awg Cu/Al, Q1, BR, Type BR Loadcenters
Weight per unit	0.3000 (lbs/each)
Product Category	1 Pole Standard Trip Plug-In
Features	
dimensions	2.5000 IN X 1.0000 IN X 3.0000 IN
interrupt rating	10 kAIC
Poles	Single-pole
Voltage Rating	120/240 V
Descriptions	
extra long description	ETN BR120 Type BR Breaker 20A/1 Pol
Features	Eaton's residential BR Circuit Breakers are used in load centers, panelboards, or similar devices. They are made for a wide range of applications and include: BR 1" circuit breakers and accessories for BR-style load centers; arc fault circuit interrupter (AFCI); and ground fault circuit interrupters (GFCI).
Long Description	Eaton BR thermal magnetic circuit breaker, Type BR 1-Inch plug-on circuit breaker, 20 A, 10 kAIC, Single-pole, 120/240V, BR, #14-4 AWG Cu/AI, Q1, BR, Type BR loadcenters
Product Type	Type BR Breaker 20A/1 Pole 120/240V 10K
Manufacturer Information	
Brand	Eaton
GTIN	00786676362108
Manufacturers Part Number	BR120
UPC	786676362108
Taxonomies, Classifications, and (Categories
Category Description	Loadcontor Diug In Progkers and Accessories
Туре	Thermal magnetic circuit breakers
Availability	
Status	Inactive

12

1

0.3

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses,	Certifications,	and Standards
-------	-----------------	---------------

	anda do
Application	Generation - Renewable Energy - Alternative EnergyGeneration -
	Conventional Energy - Conventional EnergyOtherMarine Vessels
	and Equipment - Marine Vessels and Equipment -
	OtherDatacenters - IT Space: CI and Hyper Converged
standard	UL 489, Federal Specifications Classification W-C375