


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Weight Per each

C0500E1B 500 Va Type Mte Control Transformer *Eaton Corp*

| Catalog Number | C0500E1B |
|------------------------------------|---|
| Manufacturer | Eaton Corp |
| Description | Eaton Type Mte, Industrial Control Transformer, PV: 120 X 240V, |
| | Taps: None |
| Weight per unit | |
| Product Category | Encapsulated Industrial Contro |
| Features | |
| dimensions | 6.1100 IN X 5.2500 IN X 5.1400 IN |
| kva rating | 500 VA |
| Primary Voltage | 120 x 240 V |
| Secondary Voltage | 24 V |
| Tap Size | NONE |
| Descriptions | |
| Description | 500 VA TYPE MTE CONTROL TRANSFORMER |
| extra long description | ETN C0500E1B 500 VA Type MTE Contro |
| Features | Eaton offers a complete line of Type AP, MTE and MTK Industrial |
| | Control Transformers, which provide stepped-down voltages to |
| | machine tool control devices. Each unit must pass rigid tests for |
| | turns ratio, insulation, continuity, and over potential. |
| | Performance meets or exceeds ANSI/NEMA ST-1 requirements. |
| | With a 50-60 Hz operation standard, transformers are designed |
| | for loads requiring extremely good regulation. Regulation also |
| Long Description | exceeds ANSI/NEMA requirements. |
| Long Description | Eaton type MTE, industrial control transformer, pv: 120 x 240v, |
| Product Type | taps: none 500 Va Type Mte Control Transformer |
| Manufacturer Information | |
| Brand | Eaton |
| GTIN | 00786680423086 |
| Manufacturers Part Number | C0500E1B |
| UPC | 786680423086 |
| Taxonomies, Classifications, and (| |
| Catagory Description | CONTROL TRANSCORMERS |
| Type | Industrial Control Transformer |
| • | |
| Packaging Carton | 1 |
| Gai turi | 1 |

16

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

| Application | Other |
|--------------------|---|
| standard | UL Listed, CSA Certified, cUL Certified, RoHS Compliant |
| Temperature Rating | 55°C |