

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Status

CC2200 1PH 2P 200A 240V Type CC Main Breaker Eaton Corp

Catalog Number	CC2200
Manufacturer	Eaton Corp
Description	Eaton Type CCV Tenant Main Circuit Breaker, Tenant Main Circui Breaker, 225 A, 10 Kaic, Two-Pole, 120/240 V, #2/0 Awg-300 Kcmil Cu/Al, CCV, Type Ecc Unit Enclosures, Load Side Terminals
Weight per unit	2.5 (lbs/each)
Product Category	Main Circuit Breaker Modules
atures	
dimensions	7.7000 IN X 4.5000 IN X 5.4000 IN
interrupt rating	10 kAIC
Poles	Two-pole
Voltage Rating	120/240 V
escriptions	
Description	1PH 2P 200A 240V TYPE CC MAIN BREAKER
extra long description	ETN CCV2225X CCV, 2P, 225A, 10kAIC,
Features	Eaton's main circuit breakers are used in a variety of application including the main or emergency disconnect on the outside of a house, a tenant main breaker in group metering stacks and feed-through lug blocks specifically designed for sub-feeding from an existing panel. Main breakers are available with a variet of accessories including shunt trip, bell alarms and auxiliary switches.
Long Description	Eaton Type CCV Tenant Main Circuit Breaker, Tenant main circuit breaker, 225 A, 10 kAIC, Two-pole, 120/240 V, #2/0 AWG-300 kcmil Cu/AI, CCV, Type ECC unit enclosures, Load side terminals
Product Type	CCV, 2P, 225A, 10KAIC, Load Lugs Only
anufacturer Information	
Brand	Eaton
GTIN	00786685368658
Manufacturers Part Number	CCV2225X
UPC	786685368658
xonomies, Classifications, and (Categories
	Breaker Enclosures with or without Breaker
Туре	Tenant main breaker
vailability	
• • •	

Inactive



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging Carton	1
Weight Per each	2.45
Uses, Certifications, and Standards	
Application	Generation - Conventional Energy - Conventional EnergyGeneration - Renewable Energy - Alternative EnergyMarine Vessels and Equipment - Marine Vessels and Equipment - OtherOtherDatacenters - IT Space: CI and Hyper Converged
standard	UL 489