

Elliott Electric Supply

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

We Deliver...Lower Cost, Quality Products, & Personal Service

1		-		1	
	ľ				
		1	18		
		81			
		E	Ш		
		3	8		
		3			
		12			

CH42B3200L 3PH/CH Loadcntr 200A 10KAIC MCB 42 Cir. Cu Bus Nem Eaton Corp

Catalog Number	CH42B3200L	
Manufacturer	Eaton Corp	
Description	Main Circuit Breaker Loadcenter, 42 Spaces, 42 Circuits, 200 A, 120/208/240 V Ac, #2/0 Awg to 300 Kcmil Wire Size, Metallic (Enclosure) Material, Copper Bus Material, 98.5520 CM Overall Length, 36.3474 CM Overall Width, 99.0600 CM Overall Height, 39.3 LB/Ea	
Weight per unit	39.3 (lbs/each)	
Product Category	Three Phase Main Breaker Load	
Features		
amperage rating	200	
Cover Type	Ch8lf-combination, ch8ls-surface, not included	
dimensions	39.0000 IN X 14.3100 IN X 3.8800 IN	
media	Yes	
number of spaces	42	
Phase	3	
Dimensions and Weight		
Depth	39.0000	
Height	3.8800	
Size		
Width	14.3100	
Descriptions		
Description	3PH/CH LOADCNTR 200A 10KAIC MCB 42 CIR. CU BUS NEM	
extra long description	ETN CH42B3200L 3Ph/CH LC 200A MCB 4	
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box or even a fuse box, the main function is to take electricity	
	supplied by the utility and distribute it throughout the home to	
	feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.	
	separately and available as surface of husin mount.	
Manufacturer Information		
Brand	EATON CUTLER-HAMMER	
GTIN	00782113098265	
UPC		
Taxonomies, Classifications, and	•	
	LOADCENTERS & COVERS	
Туре	Main breaker loadcenter	



$E_{\text{LLIOTT}} E_{\text{LECTRIC}} S_{\text{UPPLY}}$

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging Carton	1
Weight Per each	39.3
Uses, Certifications, and Standards	
standard	UL 50,UL 67