

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### CHP22N125R CH Pon Loadentr 125A Convertible 22 Space N3R

Catalog Number	CHP22N125R	
Manufacturer	Faton Corn	
Description	Eaton CH Convertible Loadcenter, 125A, Convertible, 22 Spaces, Nema 3R	
Weight per unit		
Product Category	Single Phase Convertible Load	
eatures		
amperage rating	125	
dimensions	04 0000 IN V 4 4 0400 IN V 5 4000 IN	
interrupt rating	10	
media		
number of spaces	22	
Phase	1	
imensions and Weight		
Depth	21	
Height	5.19	
Size	X2	
Width	4 4 9 4	
escriptions		
Description	CH PON LOADCNTR 125A CONVERTIBLE 22 SPACE N3R	
extra long description		
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical bo or even a fuse box, the main function is to take electricity supplied by the utility and distribute it throughout the home to feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.	
Long Description	Eaton CH convertible loadcenter, 125A, convertible, 22 spaces, NEMA 3R	
Product Type	CH Pon LC, 125A, Conv, 22SP, N3R	

#### Mar

Brand	Eaton	
GTIN	00786689058586	
Manufacturers Part Number	CHP22N125R	
UPC	786689058586	



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, C	classifications, and	<b>Categories</b>
---------------	----------------------	-------------------

Category Description	LOADCENTERS & COVERS
Туре	Convertible loadcenter
Packaging	
Carton	1
Weight Per each	23
Uses, Certifications, and Standa	rds Residential Bldgs & Facilities - Residential Bldgs & Facilities -

### Use

Application	Residential Bldgs & Facilities - Residential Bldgs & Facilities -
	Other
standard	UL 67,UL 50