



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



D1PR1T 1P 20A 24V Relay

Eaton Corp

| | |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number | D1PR1T |
| Manufacturer | Eaton Corp |
| Description | D1 Series General Purpose Plug-In Relay, Plain Cover With Led Indicator, 24V Coil, 50/60 HZ, 180 Ohms Resistance, Plug-In Terminal, SPDT Contact Configuration, 20A Contact Rating, Silver Alloy Contacts, IP40 Enclosure, Plain Cover |
| Weight per unit | 0.1000 (lbs/each) |
| Product Category | In Relays & Accessories |

Features

| | |
|-----------------------|----------|
| Contact Configuration | SPDT |
| Contact Rating | 20 A |
| Resistance | 180 ohms |

Descriptions

| | |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description | 1P 20A 24V RELAY |
| extra long description | ETN D1PR1T D1 Series General Purpos |
| Features | Installation?of?general?purpose?relays are quick, easy and secure with little risk of damage, and various relay models are specifically slim-form designed to fit into tight spaces. The?D?series?ice?cube?general?purpose?relays?provide excellent functionality and are ideal for any application from?controlling smaller loads, to those requiring high current-carrying capacity.?A wide array of coil voltages and contact configurations ensure there is a D series relay for every control circuit design application. |
| Long Description | D1 Series General Purpose Plug-In Relay, Plain cover with LED indicator, 24V coil, 50/60 Hz, 180 Ohms resistance, Plug-in terminal, SPDT contact configuration, 20A contact rating, Silver alloy contacts, IP40 enclosure, Plain cover |
| Product Type | D1 Series General Purpose Plug-In Relay |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Eaton |
| GTIN | 00786685269795 |
| Manufacturers Part Number | D1PR1T |
| UPC | 786685269795 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|------------------------|
| Category Description | GENERAL PURPOSE RELAYS |
| Type | General-purpose relay |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Availability

| | |
|--------|----------|
| Status | Inactive |
|--------|----------|

Packaging

| | |
|--------|---|
| Carton | 1 |
|--------|---|

| | |
|-----------------|-----|
| Weight Per each | 0.1 |
|-----------------|-----|

Uses, Certifications, and Standards

| | |
|-------------|---------------------------------------------------------------------------------------------------------------|
| Application | Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other |
|-------------|---------------------------------------------------------------------------------------------------------------|

| | |
|-----------|------|
| Enclosure | IP40 |
|-----------|------|

| | |
|------------------|----------|
| Frequency Rating | 50-60 Hz |
|------------------|----------|

| | |
|----------|--------------------------------------------------------|
| standard | CSA Certified,UL Listed,cRUus,CE Marked,RoHS Compliant |
|----------|--------------------------------------------------------|