



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



DVERF5NSLA Caseta Claro 5A Switch Light Almond *Lutron*

Catalog Number	DVERF5NSLA
Manufacturer	Lutron
Description	Lutron Claro Smart Switch For Caseta Smart Lighting
Weight per unit	0.2800 (lbs/each)
Product Category	Line Construction Material

Features

amperage rating	5.0/3.0
connection	Wire Leads
Connection Type	Wire Leads
insulation	Plastic
Material	Plastic/Metal
Poles	1
Voltage Rating	120

Material, Color, and Finish

Color	White
-------	-------

Dimensions and Weight

Size	4.69 x 2.94
------	-------------

Descriptions

Description	CASETA CLARO 5A SWITCH LIGHT ALMOND
extra long description	LUT DVERF-5NS-LA LUTRON CLARO SMART
Features	<p>Introducing the Claro smart switch for Caseta smart lighting. Lutron's most popular switch design is now smart and works in your Caseta home. Match existing Claro switches in your home with the same elegant, recognized paddle style, updated to match existing Caseta products with an LED indicator light. Welcome Home to Peace of Mind - always come back to a well-lit home with the Claro smart switch. Enable the Smart Away feature to randomly turn lights on and off, to make it look like you're home, even if yo</p>
Long Description	Lutron Claro Smart Switch for Caseta Smart Lighting
Product Type	Lutron Claro Smart Switch Light Almond
Special Features	Works with 5A LED, 3A general purpose fan, or 600W incandescent

Manufacturer Information

Brand	Lutron
GTIN	00784276302623
Manufacturers Part Number	DVERF-5NS-LA
UPC	784276302623



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Type	Wireless in-wall electronic switch, multi-location, 3-way, single-pole
------	--

Packaging

Carton	1
Package	24
Weight Per each	0.28

Uses, Certifications, and Standards

Application	Lighting Control
Enclosure	Plastic
Mounting	WALLBOX
Operating Temperature	32 to 104