

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



E22PB3A PB Flush BKBZ G 1no Eaton Corp

Catalog Number	E22PB3A
Manufacturer	Eaton Corp
Description	Eaton, Non-Metallic Heavy-Duty Pushbutton, Assembled, Green, Plastic Actuator, Black Bezel, 1NO, Non-Illuminated, Flush Mounting, Nema 3, 3R, 4, 4X, 12, 13, Momentary, 22.5 MM, Flush Pushbutton, E22 Series
Weight per unit	0.0500 (lbs/each)
	Push Button Complete Assemblie

Features

action	Green	
actuator	Flush	
Contact Configuration	1 NO	
dimensions	1.0000 IN X 1.0000 IN X 1.0000 IN	

Dimensions and Weight

Depth	1
Height	1
Size	22.5 mm
Width	1

Descriptions

Description	PB FLUSH BKBZ G 1NO
extra long description	ETN E22PB3A PB FLUSH BKBZ G 1NO
Features	Eaton's 22.5 mm industrial heavy-duty pushbutton line offers a wide array of functional, smartly styled illuminated and non-illuminated pushbuttons, selector switches, push-pulls, action and twist-to- release operators. The complete line also includes transformer, full voltage, resistor, LED or neon light units.
Long Description	Eaton, Non-metallic Heavy-Duty Pushbutton, Assembled, Green, Plastic Actuator, Black bezel, 1NO, Non-illuminated, Flush mounting, NEMA 3, 3R, 4, 4X, 12, 13, Momentary, 22.5 mm, Flush Pushbutton, E22 Series
Product Type	PB Flush BKBZ G 1no
Special Features	Assembled



Manufacturer Information

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 936-560-4685

diactarer information	
Brand	EATON CUTLER-HAMMER
GTIN	00782113553221
Manufacturers Part Number	E22PB3A
Model	Pushbutton
UPC	782113553221

Category Description	MINATURE PILOT DEVICES.22MM
Type	PUSHBUTTON
Packaging	
Carton	1
Weight Per each	0.05

Uses, Certifications, and Stan	dards
Application	Stationary Machinery and Equipment Outside Factory -
	Stationary Machinery and Equipment Outside Factory - Other
Mounting	FLUSH
standard	Lloyd's Register Certified,CSA Certified,UL 508,IEC 947-5-1
	MTTA,CE Marked