

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



E30.125BK6P Thin-Wall Heat Shrink Tubing, 1/8", BK Minnesota Mining (3M)

| Catalog Number | E30.125BK6P |
|--|---|
| Manufacturer | Minnesota Mining (3M) |
| Description | 3M [™] Heat Shrink Tubing Eps-300 Is A Dual Wall Tubing Provides The Advantage Of An Integral, Adhesive Lined Construction. This Flame Retardant Tubing With A 3:1 Shrink Ratio Offers Insulation For 600V Rated Applications. The Flexible Polyolefin Constructio Features An Internal Layer Of Thermoplastic Adhesive, Which Offers Moisture Seal Protection In Automotive and Marine |
| | Applications. |
| Weight per unit | 0.0050 (lbs/each) |
| Product Category | Splicing & Terminating Kits |
| criptions | |
| Description | THIN-WALL HEAT SHRINK TUBING, 1/8", BK |
| extra long description | 3M 7010399008 3M™ Thin-Wall Heat Sh |
| Features | 3M [™] Heat Shrink Tubing EPS-300 is color coded for quick and |
| | easy identification of the wire. It provides a skintight fit and |
| | strain relief protection for electronic components, wire splices, |
| | wire bundles and harness breakouts. This flame retardant tubing |
| | has a heat shrinkable outer wall that is irradiation cross linked for |
| | abrasion resistance and helps to maintain the high flow as well a |
| | good adhesion characteristics. When the tubing cools down, it |
| | forms a permanent, water resistant barrier. It withstands |
| Long Description | 3M [™] Heat Shrink Tubing EPS-300 is a dual wall tubing provides |
| | the advantage of an integral, adhesive lined construction. This |
| | flame retardant tubing with a 3:1 shrink ratio offers insulation for |
| | 600V rated applications. The flexible polyolefin construction |
| | features an internal layer of thermoplastic adhesive, which offer |
| Product Type | moisture seal protection in automotive and marine applications. 3M™ Thin-Wall Heat Shrink Tubing Eps-300 |
| Product Type Special Features | Adhesive Lined Flexible Pilyolefin |
| nufacturer Information | |
| Brand | 3M |
| | 00051100/01010 |
| March Gard and David Nillarda a | |
| | |
| UPC | $\overline{}$ |
| UPC | Categories |
| UPC onomies, Classifications, and (Category Description | |



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging | |
|---|--------------|
| Carton | 10 |
| Weight Per each | 0.005 |
| Uses, Certifications, and Standards standard | UL, ABS, CSA |
| | |