



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



E30.188BK6"P Thin-Wall Heat Shrink Tubing, BK, 3/16-6" *Minnesota Mining (3M)*

Catalog Number	E30.188BK6"P
Manufacturer	Minnesota Mining (3M)
Description	3M™ Heat Shrink Tubing Eps-300 Is A Dual Wall Tubing Provides The Advantage Of An Integral, Adhesive Lined Construction. This Flame Retardant Tubing With A 3:1 Shrink Ratio Offers Insulation For 600V Rated Applications. The Flexible Polyolefin Construction Features An Internal Layer Of Thermoplastic Adhesive, Which Offers Moisture Seal Protection In Automotive and Marine Applications.
Weight per unit	0.0100 (lbs/each)
Product Category	Splicing & Terminating Kits

Descriptions

Description	THIN-WALL HEAT SHRINK TUBING, BK, 3/16-6"
extra long description	3M 7010350254 3M™ Thin-Wall Heat Sh
Features	3M™ Heat Shrink Tubing EPS-300 is color coded for quick and easy identification of the wire. It provides a skintight fit and strain relief protection for electronic components, wire splices, wire bundles and harness breakouts. This flame retardant tubing has a heat shrinkable outer wall that is irradiation cross linked for abrasion resistance and helps to maintain the high flow as well as good adhesion characteristics. When the tubing cools down, it forms a permanent, water resistant barrier. It withstands
Long Description	3M™ Heat Shrink Tubing EPS-300 is a dual wall tubing provides the advantage of an integral, adhesive lined construction. This flame retardant tubing with a 3:1 shrink ratio offers insulation for 600V rated applications. The flexible polyolefin construction features an internal layer of thermoplastic adhesive, which offers moisture seal protection in automotive and marine applications.
Product Type	3M™ Thin-Wall Heat Shrink Tubing Eps-300
Special Features	Adhesive Lined Flexible Polyolefin

Manufacturer Information

Brand	3M
GTIN	00051128600672
Manufacturers Part Number	E30.188BK6"P
UPC	051128600672

Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Type	Dual Wall (Adhesive Lined)



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	10
Weight Per each	0.01

Uses, Certifications, and Standards

standard	UL, ABS, CSA
----------	--------------