

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Contraction Ch. Mailer						
	-	100	-	100	in a	
and the second se	1.15	. 1.1	100			

ECLK136 1/2X36 LT Flex Coupling Crouse-Hinds

Catalog Number	ECLK136		
Manufacturer	Crouse-Hinds		
Description	Eaton Crouse-Hinds Series Eclk Coupling, 36" Flexible Length, Male Connection One End, Female Connection One End, Forged Brass, 1/2" Trade Size		
Weight per unit	4.0 (lbs/each)		
Product Category	Rigid Conduit Fittings - Steel		
Features			
connection	Female Union X Male Threaded		
dimensions	39.7500 IN X 1.5000 IN X 1.5000 IN		
outside diameter	1-1/2		
Dimensions and Weight			
Length	36		
Descriptions			
Description	1/2X36 LT FLEX COUPLING		
extra long description	CRS-H ECLK136 1/2 X 36 DIV 1 FLEX C		
Features	Crouse-Hinds series EC explosionproof couplings are used in hazardous areas where a flexible member is required in a condui system to accomplish difficult bends, or to allow for movement		
	or vibration of connected equipment or units.		
Long Description	Eaton Crouse-Hinds series ECLK coupling, 36" flexible length, Male connection one end, female connection one end, Forged brass, 1/2" trade size		
Product Type	1/2 X 36 Div 1 Flex CPLG Male-Female		
Special Features	Liquidtight		
Manufacturer Information			
Brand	Eaton		
GTIN	00782274744728		
Manufacturers Part Number	ECLK136		
UPC	782274744728		
Taxonomies, Classifications, and (Categories		
Category Description			
Туре			
Trade Size			
Trade Size	1/2 in		



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

D I		· · · · · ·
Dack	nev	ind
гаск	۱au	II IU
Pack	3	

Carton	1
Weight Per each	3.9599
Uses, Certifications, and Stand	dards
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 Group A B C D, Class II Div I Group E F G, Class III
standard	UL 1203