

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



ECNR200 200A RK5 Time Delay Bullet Fuse Bussmann Fuses

Catalog Number	ECNR200
Manufacturer	Bussmann Fuses
Description	Eaton Edison Ecnr Fuse, Time-Delay Current-Limiting Fuse, Superior Overload and Cycling Capabilities, 200 A, Dual, Class RK5, Non-Indicating, Blade End X Blade End, 10 Sec At 500%, 200 Kaic, Standard, 250 V, 125 VDC
Weight per unit	0.8500 (lbs/each)
Product Category	Dual Element
Features	
amperage rating	200 A
class	Class DVF
connection	Blade End X Blade End
dimensions	0 4200 IN V 2 2000 IN V 2 2000 IN
element	Dual
interrupt rating	200 kAIC
media	Yes
Response Time	10 S at 500%
type of indicators	Non-Indicating
Voltage Rating	250 VAC, 125 VDC
Dimensions and Weight	
Size	1.56 In Diameter X 7.13 In Length
Descriptions	
Description	200A RK5 TIME DELAY BULLET FUSE
extra long description	BUSS ECNR200 UL CLASS RK-5 TIME DEL
Features	Edison's UL Class RK5 dual-element, time-delay fuses provide
	economical solutions to overcurrent protectioni. Available in
	both 250Vac and 600Vac, with 200kA RMS Sym interrupting
	ratings and sizes ranging from 0 to 600 amp.
Long Description	EATON EDISON ECNR FUSE, TIME-DELAY CURRENT-LIMITING
	FUSE, SUPERIOR OVERLOAD AND CYCLING CAPABILITIES, 200 A,
	DUAL, CLASS RK5, NON-INDICATING, BLADE END X BLADE END,
Product Type	10 SEC AT 500%, 200 KAIC, STANDARD, 250 V, 125 VDC UI Class RK-5 Time Delay
Product Type Special Features	UI Class RK-5 Time Delay Non current limiting
special i calules	NOT CUITCH HITHUNG



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton
GTIN	00782634507482
Manufacturers Part Number	ECNR200
UPC	782634507482

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE

Availability

Status Inactivo	
Status	

Packaging

Carton	1
Weight Per each	0.85

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked