



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



EI500C Digital 7DAY Timer Iv *Intermatic Inc.*

Catalog Number	EI500C
Manufacturer	Intermatic Inc.
Description	7-Day Standard Programmable Timer, 125 Vac, 15A, Ivory
Weight per unit	0.2500 (lbs/each)
Product Category	Electronic Time Switches

Features

action	1 x SPST
amperage rating	15
Contact Configuration	1 NO
Contact Rating	15 AMP @ 120 VAC (Resistive Heater), 8.3 AMP @ 120 VAC (Tungsten Incandescent), 8 AMP @ 120 VAC (Ballast Magnetic)
motor power	1/4 HP @ 120 VAC
Poles	1
Timing Range	1 MIN - 7 DAYS
Voltage Rating	120
Wattage	1875

Dimensions and Weight

Size	2.75 HEIGHT X 1.75 WIDTH X 1.36 DEPTH IN, 69.85 HEIGHT X 44.45 WIDTH X 34.54 DEPTH MM
------	---------------------------------------------------------------------------------------

Descriptions

Description	DIGITAL 7DAY TIMER IV
extra long description	INT-MAT EI500C 7-Day Standard Progr
Features	For installation on 15 A circuits, this timer provides 24-hour or 7-day programming of lights, fans, pumps and other medium-duty loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.
Long Description	7-Day Standard Programmable Timer, 125 VAC, 15A, Ivory
Product Type	7-Day Standard Programmable Timer, 125 Vac, 15A, Ivory
Special Features	Features: Compact and Quiet Low Profile Design, Continuously Displays Time of Day and Day of Week and Load Status, Internal Rechargeable Battery - Minimum 36 Hour Backup, 1 Year Warranty

Manufacturer Information

Brand	Intermatic Inc.
GTIN	00078275105218
Manufacturers Part Number	EI500C
UPC	078275105218



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	TIME CLOCKS
Type	Decorator Digital In-Wall

Packaging

Carton	1
Package	6
Weight Per each	0.25

Uses, Certifications, and Standards

Application	Incandescent Lighting, Fluorescent Lighting, HVACR, CFL Lighting, LED Lighting
Frequency Rating	60
Mounting	WALL MOUNT
Operating Temperature standard	+32 to +122 DEG F, 0 to +50 DEG C cULus Listed, HVACR