

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### ENP6202 20A-250V Plug Crouse-Hinds

Catalog Number	ENP6202
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Ark-Gard Enp Plug, 20A, 50-400 HZ, Copper-Free Aluminum, 6-20P, 250 Vac
Weight per unit	0.3800 (lbs/each)
Product Category	Pin & Sleeve Devices

#### **Features**

141.00	
amperage rating	100
Cord Type	0.875 To 1.700 In
dimensions	3.9100 IN X 1.6000 IN X 1.6000 IN
Material	Copper-Free Aluminum
Poles	3
Voltage Rating	600 VAC AT 50 TO 400 HZ, 250 VDC
Wire Size	4 To 1 AWG (Building), 4 To 2 AWG (Extra Flex)

#### **Dimensions and Weight**

Length	10-1	/8
LEHULH	10-1	70

#### **Descriptions**

CRS-H ENP6202 20A 250V ARKGARD PLG
Ark-Gard ENC connectors, ENP plugs and ENR receptacles from Eaton's Crouse-Hinds Division make it safe and easy to bring power wherever it is needed. Connectors provide versatility for making cordsets for connecting portable devices in both hazardous and non-hazardous locations. Ark-Gard plugs and receptacles are used with portable electrical equipment such as compressors, tools, lighting systems and similar devices when power requirements do not exceed 20 amperes. They are also used in areas made hazar
Eaton Crouse-Hinds series Ark-Gard ENP plug, 20A, 50-400 Hz, Copper-free aluminum, 6-20P, 250 Vac
20A 250V Arkgard PLG 6-20 Nema Config
Watertight, Grounding Style 1, NEMA 4 Enclosure, Reverse Interior

#### **Manufacturer Information**

Brand	Eaton
GTIN	00782274310886
Manufacturers Part Number	ENP6202
UPC	782274310886



standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
Category Description	Pin & Sleeve Devices
Туре	PLUG
Packaging	
Carton	1
Package	2
Weight Per each	0.38
Uses, Certifications, and Standards Application	Ind Facilities & Factories - Facility: Power Distribution and Control

UL 514, UL 1010, UL 1682, CSA C22.2