



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



EVICX2301 Explosion Proof Incandescent Fixture

Crouse-Hinds

Catalog Number	EVICX2301
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Evi Light Fixture, Medium Base, Heat and Impact Resistant Glass Globe, With Cast Copper-Free Alum Guard, Incandescent, Copper-Free Aluminum, PS-25 Max. Lamp Size, Ceiling Mount, Factory Sealed, 3/4", 120 Vac, 300W
Weight per unit	14.4 (lbs/each)
Product Category	Incandescent Hazardous Locatio

Features

dimensions	7.2500 IN X 7.2500 IN X 13.7500 IN
Voltage Rating	120 V
Wattage	300 W

Descriptions

Description	EXPLOSION PROOF INCANDESCENT FIXTURE
extra long description	CRS-H EVICX2301 100/500W FS EXPF IN
Features	Crouse-Hinds series EVI incandescent luminaires are used where a consistent light level relatively unaffected by extremes in ambient temperature (-40°C to +65°C) is required. Commonly used in areas that require lamps to reach full illumination immediately, locations that require lamps to be frequently turned on and off, and in tough environmental conditions involving corrosives, water, dust and extreme temperatures.
Long Description	Eaton Crouse-Hinds series EVI light fixture, Medium base, Heat and impact resistant glass globe, With cast copper-free alum guard, Incandescent, Copper-free aluminum, PS-25 max. lamp size, Ceiling mount, Factory sealed, 3/4", 120 Vac, 300W
Product Type	100/500W FS Expf Incan 3/4 Ceil
Special Features	3/4 In Hub, With Guard

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274235851
Manufacturers Part Number	EVICX2301
UPC	782274235851

Taxonomies, Classifications, and Categories

Category Description	Emergency & Exit Lighting
Type	Light fixture



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	1
Weight Per each	14.4

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Lighting and Lighting Controls
Mounting	CEILING
standard	UL 844, CSA C22.2