

## **E**lliott **E**lectric **S**upply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## EYD316 Drain Seal Crouse-Hinds

8	
Catalog Number	EYD316
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eyd Conduit Sealing Fitting With Drain Male and Female, Feraloy Iron Alloy and/or Ductile Iron, Vertical Only, Group B Rated, 1"
Weight per unit	2.5 (lbs/each)
Product Category	Sealing Bodies
Features	
connection	Female Threaded, Female Threaded
dimensions	2.1900 IN X 2.1900 IN X 4.3100 IN
Material, Color, and Finish	
Finish	Untreated
Descriptions	
Description	DRAIN SEAL
extra long description	CRS-H EYD316 1 NPT GRP B MALE/FEM C
Features	In addition to restricting the passage of gases, vapors or flames
	from one portion of the electrical installation to another,
	Crouse-Hinds series EYD and EZD drain sealing fittings prevent
	accumulation of condensate above the seal. They are installed in vertical conduit runs and at low points in conduit systems.
Long Description	Eaton Crouse-Hinds series EYD conduit sealing fitting with drain, Male and female, Feraloy iron alloy and/or ductile iron, Vertical only, Group B rated, 1"
Product Type	1 NPT GRP B Male/Fem CST Iron Drain Seal
Special Features	With Drain, Vertical Position
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274365183
Manufacturers Part Number	EYD316
UPC	782274365183
Faxonomies, Classifications, and (	Categories
Category Description	HAZARDOUS LOCATION FITTINGS
Туре	Conduit sealing fitting with drain
Packaging	
Carton	
Package	
Weight Per each	2.48



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 2 Group F G, Class III
standard	UL 886, CSA C22.2