

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



#### FD12 2G FD-Box Crouse-Hinds

Catalog Number	FD12
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FD Device Box, Deep, Feraloy Iron Alloy, Two-Gang, 1/2"
Weight per unit	3.7 (lbs/each)
Product Category	FS & FD Type Boxes & Covers
Features	
Cable Entry	(1) Side
dimensions	4.1900 IN X 2.6900 IN X 5.1900 IN
Material	Natural Finished Cond Conner Free Aluminum
<b>Dimensions and Weight</b>	
Size	3/4 in
Descriptions	
Description	2G FD-BOX
extra long description	CRS-H FD12 1/2 NPT CST IRON FD BX T
Features	Crouse-Hinds series FS and FD device boxes are installed in
	non-hazardous area conduit systems to accommodate wiring
	devices, act as pull boxes or provide openings for taps and
	splices. They are suitable for use in wet locations when used
	with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub
	configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable
	iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FD device box, Deep, Feraloy iron alloy, Two-gang, 1/2"
Product Type	1/2 NPT CST Iron FD BX Two GNG MTG Lugs
Special Features	Configuration Type FD, With Mounting Lug And Ground Screw, Dimension 4-5/8 In Width X 2-11/16 In Depth X 5-3/16 In Height

#### **Manufacturer Information**

Brand	Eaton
GTIN	00782274397108
Manufacturers Part Number	FD12
UPC	782274397108

### **Taxonomies, Classifications, and Categories**

Category Description	FS BOXES AND COVERS
Туре	DEVICE BOX



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

1
3.7
Ind Facilities & Factories - Industrial Facilities/Factories - Other
SURFACE
UL 514, ANSI C33.84, CSA C22.2, Federal Specification W-C-5860