

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

		1	
	-	ĩ	
		1	
		1	
т		г	

FRNR712 7-1/2A 250V TD Class RK5 Dual Elem Fuse-Fusetron Bussmann Fuses

-			
Catalog Number	FRNR712		
Manufacturer	Bussmann Fuses		
Description	Eaton Bussmann Series FRN-R Fuse, 7.5 A, Dual, Class RK5, Non-Indicating, Ferrule End X Ferrule End, 8 Sec At 500%, 200 Kaic At 250 V, 20 Kaic At 125 VDC, Standard, 250 V, 125 VDC		
Weight per unit			
Product Category	. ,		
eatures			
amperage rating	7.5 A		
class			
connection	Forrulo End V Forrulo End		
dimensions			
element	Dual		
interrupt rating			
media	N.		
Response Time			
Voltage Rating	250 VAC, 125 VDC		
Dimensions and Weight			
Size	0.56 In Diameter X 2.00 In Length		
Descriptions			
Description	7-1/2A 250V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON		
extra long description	BUSS FRN-R-7-1/2 FUSETRON DUAL-ELEM		
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500% of rated current (8 seconds for 1/10-30A sizes).		
Long Description	Eaton Bussmann series FRN-R fuse, 7.5 A, Dual, Class RK5, Non-indicating, Ferrule end x ferrule end, 8 sec at 500%, 200 kAl at 250 V,20 kAIC at 125 Vdc, Standard, 250 V, 125 Vdc		
Product Type	Fusetron Dual-Element Class RK5		



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	COOPER BUSSMANN
GTIN	00051712506977
Manufacturers Part Number	FRN-R-7-1/2
UPC	051712506977
Taxonomies, Classifications, and Ca	tegories
Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	10
Weight Per each	0.06
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked