

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FRSR214 2-1/4A 600V TD Class RK5 Dual Elem Fuse-Fusetron Bussmann Fuses

Catalog Number	FRSR214
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series FRS-R Fuse, 2.25 A, Dual, Class RK5, Non-Indicating, Ferrule End X Ferrule End, 10 Sec At 500%, 200 Kaic At 600 V, 20 Kaic At 300 VDC, Standard, 600 V, 300 VDC
Weight per unit	0.1500 (lbs/each)
Product Category	Dual Element
eatures	
amperage rating	2.25 A
class	Class RK5
connection	
dimensions	0.8100 IN X 0.8100 IN X 5.0000 IN
element	Dual
interrupt rating	200 kAIC at 600 Vac20 kAIC at 300 Vdc
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc
Dimensions and Weight	
Size	0.81 In Diameter X 5.00 In Length
Descriptions	•
Description	2-1/4A 600V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRS-R-2-1/4 FUSETRON DUAL ELEM
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500% of rated current (8 seconds for 1/10-30A sizes).
Long Description	Eaton Bussmann series FRS-R fuse, 2.25 A, Dual, Class RK5, Non-indicating, Ferrule end x ferrule end, 10 sec at 500%, 200 kAIC at 600 V,20 kAIC at 300 Vdc, Standard, 600 V, 300 Vdc
Product Type	Fusetron Dual Element Fuse Class RK5
Special Features	Renewable



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Brand	COOPER BUSSMANN
GTIN	00051712508155
Manufacturers Part Number	FRS-R-2-1/4
UPC	051712508155

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Tyne	FUSF

Packaging

onaging		
Carton	10	
Weight Per each	0.15	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked