



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



FXS51C Exp/PR F/S Switch *Hubbell--Killark*

Catalog Number	FXS51C
Manufacturer	Hubbell--Killark
Description	FXS Series - Factory Sealed Feed-Thru Box and Cover With 1-Pole Tumbler Switch - Conduit Hub Size 3/4 In - 20 Amps
Weight per unit	4.4 (lbs/each)
Product Category	Selector Switch Complete Assem

Features

action	SP
actuator	Lever
amperage rating	20
Poles	1
Switch Type	Lever
Voltage Rating	120/277 VAC

Material, Color, and Finish

Color	Gray
-------	------

Dimensions and Weight

Size	6.63 in x 6 in x 4.38 in
------	--------------------------

Descriptions

Description	EXP/PR F/S SWITCH
extra long description	KLRK FXS-51C TUMBL SWITCH 3/4" 1P20
Long Description	FXS Series - Factory Sealed Feed-Thru Box And Cover With 1-Pole Tumbler Switch - Conduit Hub Size 3/4 In - 20 Amps
Product Type	Tumbl Switch 3/4" 1P20A F-Thru
Special Features	Killark SEAL-X Series Factory Sealed Tumbler Switch Controls provide solutions in hazardous location areas to supply;START/STOP Motor Functions and Light Switching. Utilized in Class 1 Division 1 & 2, Class 1 Zone 1 & 2 areas where Type 3, 7 & 9 protection ratings are required for indoor and outdoor use. UL Listed and CSA Certified.

Manufacturer Information

Brand	KILLARK
GTIN	00783936195582
Manufacturers Part Number	FXS-51C
series	FXS
UPC	783936195582

Taxonomies, Classifications, and Categories

Type	Factory Sealed
------	----------------



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	1
Weight Per each	4.4

Uses, Certifications, and Standards

Application	FXS tumbler switches are suitable for applications where making, breaking, or changing connections in an electrical circuit is required and where conditions of load do not exceed the switch ratings.
Enclosure	Aluminum factory sealed feed-thru splice box
standard	UL, CSA