




# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## G1X1.5LG6 LT Grey Wiring Duct

*Panduit Corporation*

Catalog Number	G1X1.5LG6
Manufacturer	Panduit Corporation
Description	The G1X1.5LG6 Panduct Lead-Free PVC Wide Slot Wiring Duct Feature A Wide Slot/Finger Design That Provides Greater Sidewall Rigidity and Is Suitable With A Range Of Wire Bundle Sizes. UL 94 Flame Class Of V-0 With A UL Recognized Continuous-Use Temperature Up to 122°F (50°C). Mounting Holes Provided. 1.0" X 1.5" (25.4 MM X 38.1 MM) and 6' (1.8 M) Long. Cover Sold Separately. Color Light Gray.
Weight per unit	1.0 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray

### Features

connection	Mounting Holes
Material	PVC
media	Yes

### Material, Color, and Finish

Color	Light Gray
-------	------------

### Dimensions and Weight

Length	NA
Size	1.26 x 1.62
Width	1.25

### Descriptions

Description	LT GREY WIRING DUCT
extra long description	PAN G1X1.5LG6 Panduct® G1X1.5LG6 Ba
Long Description	The G1X1.5LG6 Panduct Lead-Free PVC Wide Slot Wiring Duct feature a wide slot/finger design that provides greater sidewall rigidity and is suitable with a range of wire bundle sizes. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. 1.0" x 1.5" (25.4 mm x 38.1 mm) and 6' (1.8 m) long. Cover sold separately. Color Light Gray.
Product Type	Panduct® G1X1.5LG6 Base Wiring Duct

### Manufacturer Information

Brand	PANDUIT
GTIN	00074983545438
Manufacturers Part Number	G1X1.5LG6
UPC	074983545438



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	WIRE DUCT AND COVERS
Type	Base Wiring Duct

## Packaging

Carton	120
Weight Per each	1

## Uses, Certifications, and Standards

Application	Wide slot/finger design provides greater sidewall rigidity and can be used in a wide range of applications
standard	RoHS Compliant, UL Recognized, CE Compliant, CSA Approved