



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## **GMEV32BRDC Ev Direct Connect Kit 32A BR 2P 40a** *Eaton Corp*

Catalog Number	GMEV32BRDC
Manufacturer	Eaton Corp
Description	Eaton Green Motion BR Ev Smart Breaker Charger 32A, BR Plug-On 2P, 40amp
Weight per unit	10.0 (lbs/each)
Product Category	Distribution Equipment

### **Features**

amperage rating	40 A
dimensions	10.6900 IN X 9.5600 IN X 14.6900 IN
Voltage Rating	208-240 Vac

### **Descriptions**

Description	EV DIRECT CONNECT KIT 32A BR 2P 40A
extra long description	ETN GMEV32BR-DC EV Direct Connect K
Features	The future of transportation is electric. While that changes how vehicles are powered, it does not require you to adjust your driving habits or pay a premium on your electric bill. Instead, fast and cost-effective charging is a must. Enter Green Motion EV smart breaker chargers-fast AC charging, powered by smart breakers. Eaton chargers deliver real-time energy insights and enable integration with onsite renewable and energy storage systems to advance smart and sustainable energy systems to power today and
Long Description	Eaton Green Motion BR EV smart breaker charger 32A, BR plug-on 2P, 40Amp
Product Type	Ev Direct Connect Kit 32A, BR 2P 40a

### **Manufacturer Information**

Brand	Eaton
GTIN	00786689667627
Manufacturers Part Number	GMEV32BR-DC
UPC	786689667627

### **Taxonomies, Classifications, and Categories**

Category Description	DISCONNECTS
Type	BR EV smart breaker charger

### **Packaging**

Carton	1
Weight Per each	10



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Uses, Certifications, and Standards

Application

Residential Bldgs & Facilities - Residential Bldgs & Facilities -  
OtherResidential Bldgs & Facilities - Residential Bldgs/Facilities -  
Aftermarket

standard

UL 489