




ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



H200X034H1TB TT, HS, Tubing, 2"WX.34"H, 25 *Panduit Corporation*

Catalog Number	H200X034H1TB
Manufacturer	Panduit Corporation
Description	The H200X034H1T-B Military-Grade Polyolefin Heat-Shrink Label Is Single-Sided Printable. It Offers Crisp, Clear Legends With Superior Readability For Quick and Easy Label Production. The Heat-Shrink Sleeve Is Designed to Provide A Clear, Reliable, and Durable Way to Identify Wires and Cables. Shrink Ratio 3:1. 0.34" X 2" (8.6 MM X 50.8 MM). Color White. 2500 Labels Per Roll.
Weight per unit	5.3 (lbs/each)
Product Category	Markers & Marking Tapes

Features

labels per package	2500
Material	Polyolefin
Printer Type	THERMAL TRANSFER
Temperature Range	275

Material, Color, and Finish

Color	White
-------	-------

Dimensions and Weight

Length	NA
Size	2.00 x 0.34
Width	2

Descriptions

Description	TT,HS,TUBING,2"WX.34"H,25
extra long description	PAN H200X034H1T-B H200X034H1T-B Hea
Long Description	The H200X034H1T-B Military-Grade Polyolefin Heat-Shrink Label is single-sided printable. It offers crisp, clear legends with superior readability for quick and easy label production. The heat-shrink sleeve is designed to provide a clear, reliable, and durable way to identify wires and cables. Shrink ratio 3:1. 0.34" x 2" (8.6 mm x 50.8 mm). Color White. 2500 labels per roll.
Product Type	H200X034H1T-B Heatshrink, Po, White, Mil Grade, 2500 LBLs, T

Manufacturer Information

Brand	PANDUIT
GTIN	00074983525614
Manufacturers Part Number	H200X034H1T-B
UPC	074983525614



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Type	Heat Shrink Label

Packaging

Carton	1
Weight Per each	5.3499

Uses, Certifications, and Standards

standard	Meets UL Standard 224 for flammability and AMS-DTL-23053/5C (Class 1 and Class 3). Meets SAE-AS81531, MIL-STD-883F Method 2015.13, Solutions A, B, and D, and D202F, and MIL-STD-202G Method 215K, Solutions A, C, and D when printed with resin or hybrid ther
----------	---