

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



HBL320P7W PS, IEC, Plug, 2P3W, 20A 480V, 4X/69K Hubbell Wiring Devices

Catalog Number	HBL320P7W				
Manufacturer	9				
Description					
Weight per unit					
Product Category					
Features					
amperage rating	20				
connection	Screwed Terminal				
Cord Type	All Portable				
Current Rating					
Material	COMPOSITE				
Number of Wires					
Phase	1				
Poles	2-Pole				
Voltage Rating	480				
Wire Size	#14 to #10				
Dimensions and Weight					
Size	Standard Sized				
Descriptions					
Description	PS, IEC, PLUG, 2P3W, 20A 480V,4X/69K				
extra long description	HWDK HBL320P7W PS, IEC, PLUG, 2P3W,				
Features	Watertight Devices - Hubbell's IEC 60309 Pin and Sleeve plugs, connectors, inlets and receptacles are the highest performing products available. The HBL® series of IEC pin and sleeve were designed for the demanding North American market. Hubbell was the first and is still only manufacturer of IEC 60309 devices in the USA and have numerous innovative features noted below. The IEC line of plugs and connectors are made with a rugged super tough, one-piece housing. The thermoset polyester contact carrier provi				
Long Description	Heavy Duty IEC Pin and Sleeve Industrial Grade Male Plug 20A 480V AC, 2-Pole 3-Wire Grounding, Terminal Screws, Watertight				
Product Type	PS, IEC, Plug, 2P3W, 20A 480V, 4X/69K				
Special Features	Watertight				



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

N	Λi	ar	าน	fa	ct	ur	er	In	fo	rn	na	tic	on
		_			-	-	•		- ~				<i>-</i>

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585403410
Manufacturers Part Number	HBL320P7W
series	HBL Heavy Duty
UPC	783585403410

Taxonomies, Classifications, and Categories

Category Description	Pin & Sleeve Devices
Туре	Watertight Plug

Packaging

3 3		
Carton	1	
Package	10	
Weight Per each	0.85	

Uses, Certifications, and Standards

Application	High Ampacity Connections
environmental conditions	Watertight
Mounting	Cord
nema rating	Non-NEMA
standard	CSA Certified File LR280C; UL Classified to IEC 60309-1 IEC
	60309-2;UL Standard UL1682 and UL 1686C2