

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Yes

600 V



HCTR1.8 1.8A 600V TD Class CC Fuse Edison Fuses

| Catalog Number | HCTR1.8 |
|------------------|--|
| Manufacturer | Edison Fuses |
| Description | Eaton Edison HCTR Fuse, Non-Indicating, 1.8 A, Class CC, 200 |
| | Kaic, Standard, 10, 600 V |
| Weight per unit | 0.0100 (lbs/each) |
| Product Category | Dual Element |
| Features | |
| amperage rating | 1.8A |
| class | Class CC |
| dimensions | 1.0000 IN X 0.4060 IN X 0.4060 IN |
| interrupt rating | 200 kAIC |

Descriptions

media

Voltage Rating

| Description extra long description Features | 1.8A 600V TD CLASS CC FUSE EFSE HCTR1.8 UL CLASS CC TIME DELAY Edison offers a complete line of Class CC fuses to meet your circuit and equipment protection needs. These branch circuit rated compact fuses rated 600v, and delivering 200,000a IR Vac Sym provide excellent protection in the smallest package of any UL class of fuses. Choose from our EDCC time-delay fuses for your small horsepower motor circuits, our HCLR fast-acting for your non-inductive lighting and resistance heating loads or our HCTR time-delay fuses for your small control transformer protection. |
|---|--|
| Long Description | Eaton Edison HCTR fuse, Non-indicating, 1.8 A, Class CC, 200 kAIC, Standard, 10, 600 V |
| Product Type | UI Class CC Time Delay |
| Special Features | Non-Indicating |

Manufacturer Information

| Brand | Eaton | |
|---------------------------|----------------|--|
| GTIN | 00782634802143 | |
| Manufacturers Part Number | HCTR1.8 | |
| UPC | 782634802143 | |

Taxonomies, Classifications, and Categories

| | - | U |
|------|---|----------|
| Туре | | FUSE |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| P | | | | |
|---|--|--|--|--|
| | | | | |
| | | | | |
| | | | | |

| Carton | 1 | |
|-----------------|----|--|
| Package | 10 | |
| Weight Per each | | |

Uses, Certifications, and Standards

| Application | Datacenters - Facilities: Critical Power |
|-------------|---|
| standard | UL Listed, CSA Certified, RoHS Compliant, CE Marked |