



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## HSTT2548QC HT Shrink Tubing

Panduit Corporation

Catalog Number	HSTT2548QC
Manufacturer	Panduit Corporation
Description	The HSTT25-48-QC Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Cross-Linked Polyolefin. 0.25" Diameter X 4' Long (6.4 MM X 1.2 M). Color Clear. 25 Per Package.
Weight per unit	1.1 (lbs/each)
Product Category	Insulating Materials

### Features

continuous operating temperatur	275
flammability	N/A
Inside Diameter	0.125
media	Yes
outside diameter	0.25
Shrink Ratio	2:1

### Material, Color, and Finish

Color	Clear
-------	-------

### Dimensions and Weight

Thickness	0.025
-----------	-------

### Descriptions

Description	HT SHRINK TUBING
extra long description	PAN HSTT25-48-QC Dry-Shrink™ HSTT25
Long Description	The HSTT25-48-QC Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Cross-linked polyolefin. 0.25" Diameter x 4' Long (6.4 mm x 1.2 m). Color Clear. 25 per package.
Product Type	Dry-Shrink™ HSTT25-48-QC Heatshrink, Clear, Po, 4' L, 0.25"

### Manufacturer Information

Brand	PANDUIT
GTIN	00074983906628
Manufacturers Part Number	HSTT25-48-QC
UPC	074983906628



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description.....HEAT/COLD SHRINK

Type.....Heat Shrink Tubing

## Packaging

Carton.....25

Weight Per each.....1.09

## Uses, Certifications, and Standards

Application.....For Dry Locations; Insulating and protecting wires and cables

standard.....Mil Spec: AMS-DTL-23053/5 Class 2