

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Catalog Number	HUB6
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Hub Conduit Hub, Malleable Iron, 2", Space-Saver
Weight per unit	1.3 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

connection	Male Threaded, Tapered Female Threaded
dimensions	2.9300 IN X 2.9300 IN X 2.1900 IN
Material	Malleable Iron

Material, Color, and Finish

Finish Zinc Electroplated

Dimensions and Weight

Size	2	İI	n	ı
YILV				ŀ

Descriptions

Description	2" STL INS CONDUIT HUB
extra long description	CRS-H HUB6 2 COND HUB CAST IRON
Features	The use of rigid/IMC conduit remains the preferred choice in many applications because of the physical protection of conductors and long service life of the installation. Consequently, the need to terminate conduit into a box or enclosure creates the need for a hub. The Crouse-Hinds series commercial hub has been developed to provide a lightweight hub that installs quickly and easily, providing a secure termination.
Long Description	Eaton Crouse-Hinds series HUB conduit hub, Malleable iron, 2", Space-Saver
Product Type	2 Cond Hub Cast Iron
Special Features	3 In Diameter X 1-11/16 In Length, Weight 10 Lb per 100

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274490403
Manufacturers Part Number	HUB6
UPC	782274490403

Taxonomies, Classifications, and Categories

Category Description	Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS
	AND THREADLESS CONNECTOR
Type	Conduit hub



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	1.3
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
Enclosure	NEMA FB-1, Class I Div 2, Class II Div 1 2, Class III Div 1 2
standard	UL 514B, CUL, CSA C22.2