



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## ITCSN300048 Heat Shrink Heavywall Cable Sleeve ITCSN3000, 48" *Minnesota Mining (3M)*

Catalog Number	ITCSN300048
Manufacturer	Minnesota Mining (3M)
Description	3M™ Heat Shrink Cable Sleeve Itcsn Is A Heavy Wall Sleeve That Provides Abrasion, Corrosion and Chemical Resistance. This Sleeve Has A 3:1 Shrink Ratio to Offer Electrical Insulation For 1 KV Rated Applications. It Features A Cross Linked Polyolefin Construction That Provides Moisture Seal Protection.
Weight per unit	2.2 (lbs/each)
Product Category	Insulating Materials

### Descriptions

Description	HEAT SHRINK HEAVYWALL CABLE SLEEVE ITCSN3000, 48"
extra long description	3M 7000031476 3M™ Heat Shrink Heavy
Features	3M™ Heat Shrink Cable Sleeve ITCSN is a split resistant sleeve with a factory applied adhesive/sealant that offers reliable performance for electrical splices, connections and terminations. It is perfect for insulating secondary splices, direct buried, submersible or dig in repairs, as well as physical protection of high voltage, air insulated connectors or lugs. It withstands temperatures of 67 to 230 degrees F ( 55 to 110 degrees C). UL Listed, CSA Certified and RoHS 2011/65/EU Compliant.
Long Description	3M™ Heat Shrink Cable Sleeve ITCSN is a heavy wall sleeve that provides abrasion, corrosion and chemical resistance. This sleeve has a 3:1 shrink ratio to offer electrical insulation for 1 kV rated applications. It features a cross linked polyolefin construction that provides moisture seal protection.
Product Type	3M™ Heat Shrink Heavy-Wall Cable Sleeves Itcsn

### Manufacturer Information

Brand	3M
GTIN	00054007089070
Manufacturers Part Number	IT3.000BK48"S
UPC	054007089070

### Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Type	Heavy Wall

### Packaging

Carton	5
Weight Per each	2.2

### Uses, Certifications, and Standards

standard	UL, CSA
----------	---------