



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## **K1259 1-1/4 90D Liq-Tite Conn** *Hubbell--Killark*

Catalog Number	K1259
Manufacturer	Hubbell--Killark
Description	1 1/4" 90° Liquidtight Connector Non-Insulated
Weight per unit	9.3 (lbs/each)
Product Category	Liquid Tight Fittings

### **Features**

insulation	False
Insulation Type	Non-Insulated
Material	Steel

### **Material, Color, and Finish**

Color	Gray
Finish	Zinc Plated

### **Dimensions and Weight**

Length	2-9/16
Size	2-9/16" L x 2-1/16" W x 2" H
Width	2-1/16

### **Descriptions**

Description	1-1/4 90D LIQ-TITE CONN
extra long description	KLRK K1259 1 1/4" 90° LT CONNECTOR
Long Description	1 1/4" 90° Liquidtight Connector Non-Insulated
Product Type	1 1/4" 90° LT Connector Non-Insulated
Special Features	Liquidtight fittings are used with metallic and non-metallic conduit to seal out water, oil, and dust in applications food processors, beverage & chemical plants, plastics fabricators, machine shops, etc.

### **Manufacturer Information**

Brand	KILLARK
GTIN	00783936998572
Manufacturers Part Number	K1259
series	K Series
sub brand	LIQUIDTIGHT
UPC	783936998572

### **Taxonomies, Classifications, and Categories**

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Type	90 Degree Liquidtight Non-Insulated Connector



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	1
Package	10
Weight Per each	9.3

## Uses, Certifications, and Standards

Application	Use with metallic and non-metallic conduit to seal out water, oil, and dust in applications for food processors, beverage and chemical plants, plastics fabricators, machine shops, etc. Liquidtight connectors are also suitable for use in hazardous location
environmental conditions	Hazardous locations
standard	UL, CSA