



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## K2004 2-In 45D Liq-Tite Conn

Hubbell--Killark

Catalog Number	K2004
Manufacturer	Hubbell--Killark
Description	2" 45° Liquidtight Connector Non-Insulated
Weight per unit	2.2 (lbs/each)
Product Category	Liquid Tight Fittings

### Features

insulation	False
Insulation Type	Non-Insulated
Material	Iron, Malleable

### Material, Color, and Finish

Color	Gray
Finish	Zinc Plated

### Dimensions and Weight

Length	2-7/16
Size	2-7/16" L x 2-7/8" W x 2-7/8" H
Width	2-7/8

### Descriptions

Description	2-IN 45D LIQ-TITE CONN
extra long description	KLRK K2004 2" 45° LT CONNECTOR NON-
Long Description	2" 45° Liquidtight Connector Non-Insulated
Product Type	2" 45° LT Connector Non-Insulated
Special Features	Liquidtight fittings are used with metallic and non-metallic conduit to seal out water, oil, and dust in applications food processors, beverage & chemical plants, plastics fabricators, machine shops, etc.

### Manufacturer Information

Brand	KILLARK
GTIN	00783936991436
Manufacturers Part Number	K2004
series	K Series
sub brand	LIQUIDTIGHT
UPC	783936991436

### Taxonomies, Classifications, and Categories

Category Description	COUPLINGS, ADAPTERS, REDUCERS, BUSHINGS, & CAPS
Type	45 Degree Liquidtight Non-Insulated Connector



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	1
Package	5
Weight Per each	2.15

## Uses, Certifications, and Standards

Application	Use with metallic and non-metallic conduit to seal out water, oil, and dust in applications for food processors, beverage and chemical plants, plastics fabricators, machine shops, etc. Liquidtight connectors are also suitable for use in hazardous location
environmental conditions	Hazardous locations
standard	UL, CSA