



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



K50S 1/2" Mall FM5 Conduit Body CVR

Crouse-Hinds

| | |
|------------------|---|
| Catalog Number | K50S |
| Manufacturer | Crouse-Hinds |
| Description | Cover, Form 5 Body Type, 1/2 In Trade Size, Screw On, 10 LB/100 |
| Weight per unit | 0.0900 (lbs/each) |
| Product Category | Bodies & Covers |

Features

| | |
|------------|-----------------------------------|
| dimensions | 3.8750 IN X 1.3130 IN X 0.2500 IN |
| Form | Form 5 |

Dimensions and Weight

| | |
|----------|--------|
| Hub Size | 1/2 in |
|----------|--------|

Descriptions

| | |
|------------------------|---|
| Description | 1/2" MALL FM5 CONDUIT BODY CVR |
| extra long description | CRS-H K50S 1/2 FORM 5 COVER SHEET S |
| Features | Form 5 malleable iron conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide access to conductors for maintenance and future system changes. Form 5 conduit bodies are manufactured in trade sizes 1/2" to 4", and are interchangeable with Appleton Form 35 conduit bodies. They are also available with a h |

Manufacturer Information

| | |
|-------|---------------------------|
| Brand | EATON CROUSE-HINDS SERIES |
| GTIN | 00782274756431 |
| UPC | 782274756431 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-------------------------------------|
| Category Description | FORM 5 CONDULETS, COVERS, & GASKETS |
| Type | COVER |

Packaging

| | |
|-----------------|------|
| Carton | 50 |
| Weight Per each | 0.09 |

Uses, Certifications, and Standards

| | |
|-------------|---|
| Application | Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other |
| standard | UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D |