

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



KTNR15 15A 250V Fa Class RK1 Fuse

Bussmann Fuses

Special Features

_	
Catalog Number	KTNR15
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series KTN-R Fuse, 70/30 Brass End Cap, Panelboards, 15 A, 1, Class RK1, Non-Indicating, Ferrule End X Ferrule End, Melamine Glass Tube, Standard, 250 V
Weight per unit	0.0200 (lbs/each)
Product Category	Renewable & Non-Renewable
eatures	
amperage rating	15 A
class	Class RK1
connection	Ferrule End X Ferrule End
dimensions	0.5600 IN X 0.5600 IN X 2.0000 IN
element	C' I .
interrupt rating	
Material	Melamine Glass Tube
media	
Voltage Rating	250 V
imensions and Weight	
Size	0.56 In Diameter X 2.00 In Length
escriptions	
Description	15A 250V FA CLASS RK1 FUSE
extra long description	BUSS KTN-R-15 LIMITRON FAST ACTING
Features	Bussmann's UL Class RK1 fuse offering includes the industry's most recognized Low-Peak dual-element, current-limiting, time-delay fuses (LPN-RK and LPS-RK) which are also available with optional indication on select ratings (see product data sheet). Complementing the Low-Peak product offering is Bussmann's Limitron family of fast-acting fuses (KTN-R, KTS-R, KWN-R and KWS-R) fuses.
Long Description	Eaton Bussmann series KTN-R fuse, 70/30 brass end cap, Panelboards, 15 A, 1, Class RK1, Non-indicating, Ferrule end x ferrule end, Melamine glass tube, Standard, 250 V
Product Type	Limitron Fast Acting Fuse Class RK1
· · · · · · · · · · · · · · ·	

70/30 Brass End Cap



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

и		_		1		_ 1				.					_
ľ	۱ <i>۱</i>	-	n		-	СТ		·Δr	ın	TO	۱rr	ทว	TI	n	7
	v			u	а	L.I	uı	C-1	'In	H V	,, ,	па		u	

Brand	Eaton
GTIN	00051712407045
Manufacturers Part Number	KTN-R-15
UPC	051712407045

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE

Packaging

onaging .	
Carton	10
Weight Per each	0.02

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	Not Applicable