


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





LCA838L 8AWG 1HOLE Lug *Panduit Corporation*

Catalog Number	LCA838L
Manufacturer	Panduit Corporation
Description	The LCA8-38-L Tin-Plated Copper Compression Lug, One-Hole, Standard Barrel, Has Color-Coded Barrels Marked With Panduit and Specified Competitor Die Index Numbers For Proper Crimp Die Selection. An Inspection Window Aids to Visually Assure Full Conductor Insertion, and The Tin-Plate Material Helps to Inhibit Corrosion. UI Listed and Csa Certified to 35 KV and Temperature Rated to 90°C.
Weight per unit	1.0 (lbs/each)
Product Category	Large Terminals & Connectors
atures	
Material	Tin-Plated Copper
media	Yes
Number of Holes	1
Stud Size	3/8
aterial, Color, and Finish	
Color	Red
mensions and Weight	
Size	#8 AWG Code
escriptions	
Description	8AWG 1HOLE LUG
extra long description	PAN LCA8-38-L Pan-Lug™ LCA8-38-L Co
Long Description	The LCA8-38-L Tin-Plated Copper Compression Lug, one-hole, standard barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp di selection. An inspection window aids to visually assure full conductor insertion, and the tin-plate material helps to inhibit corrosion. UL Listed and CSA Certified to 35 KV and temperatur rated to 90°C.
Product Type	Pan-Lug™ LCA8-38-L Comp. Lug, Tin PLT Copper, STRT, One 3/8"
Special Features	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V
anufacturer Information	
Brand	PANDUIT
GTIN	00074983900886
Manufacturers Part Number	LCA8-38-L
UPC	074983900886



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

65-13

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
	Comp & Mech Lugs and Butt Splices
Туре	Compression Lug
Packaging	
Carton	50
Weight Per each	1
Uses, Certifications, and Standards	
Mounting	5/8
standard	UL listed to 486A-486B File #E52164 and CSA certified C22.2 No.