

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LED15T848GC835X 15W Led T8 48" 35K Combo

Keystone Technologies

Catalog Number	LED15T848GC835X			
Manufacturer	Keystone Technologies			
Description	Linear Fluorescent Led Lamp, Linear, Single Ended, Instant Start Type; 47.5 Inch; UI (Canada and Us), UI, NSF/Ansi, DLC Approval; Food Equipment, Splash Zone, Dry and Damp Location Application; 120 to 277 Volt Voltage Rating; 1 Inch Diameter			
Weight per unit	0.7200 (lbs/each)			
Product Category	Shape & Circular Lamps			
atures				
Beam Spread Angle	220 Degree			
Glass Finish	FROSTED			
Intensity	1800 LUMEN			
Item	LED Tube			
Voltage Rating	120 to 277 Volt			
Wattage	15 Watt			
iterial, Color, and Finish				
Base Type	G13 Medium 2-Pin			
Color Rendering Index	80 A			
Color Temperature in Kelvin	3500			
nensions and Weight				
Diameter	1 INCH			
Length	47.5 Inch			
	Manufacturer Description Weight per unit Product Category atures Beam Spread Angle Glass Finish Intensity Item Voltage Rating Wattage aterial, Color, and Finish Base Type Color Rendering Index Color Temperature in Kelvin mensions and Weight Diameter			



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

_			•			
De	~~	~r	ın		$\boldsymbol{\sim}$	n
\mathbf{r}	~~	•		•	v	
			•			

Weight Per each

Application

Uses, Certifications, and Standards

Approval

	Additional Information	RoHS Compliant; Shatter Proof Coated Glass; System Wattage 18.5 Watt; Efficacy 100 Lumen per Watt; Visible Light Area 325 Degree; Temperature -4 to 113 Deg F				
	Commodity Description	Led Linear Fluorescent Straight, U-Shape & Circular Lamps				
	Description	15W LED T8 48" 35K COMBO				
	extra long description	LINEAR, SINGLE ENDED, INSTANT START TYPE; 47.5 INCH; UL (CANADA AND US), UL, NSF/ANSI, DLC APPROVAL; FOOD EQUIPMENT, SPLASH ZONE, DRY AND DAMP LOCATION APPLICATION; 120 TO 277 VOLT VOLTAGE RATING; 1 INCH DIAMETER; 15 WATT WATTAGE; LED TUBE; G13 MEDIUM 2-PIN BASE TYPE; 50000 LIFE IN HOUR; T8 SHAPE DESIGNATION; 1800 LUMEN INTENSITY; 3500; 80 COLOR RENDERING INDEX; FROSTED GLASS FINISH; 220 DEGREE BEAM SPREAD ANGLE; COMBODRIVE BRAND; ROHS COMPLIANT; SHATTER PROOF COATED GLASS; SYSTEM WATTAGE 18.5 WATT; EFFICA				
	Long Description	LINEAR FLUORESCENT LED LAMP, LINEAR, SINGLE ENDED, INSTANT START TYPE; 47.5 INCH; UL (CANADA AND US), UL, NSF/ANSI, DLC APPROVAL; FOOD EQUIPMENT, SPLASH ZONE, DRY AND DAMP LOCATION APPLICATION; 120 TO 277 VOLT VOLTAGE RATING; 1 INCH DIAMETER				
	Product Type	Linear Fluorescent Led Lamp				
Ma	anufacturer Information					
	Brand	Keystone Technologies				
	Manufacturers Part Number	KT-LED15T8-48GC-835-X				
	Model	800				
Tax	xonomies, Classifications, and Ca	itegories				
	Category Description	LED LINEAR STRAIGHT(Fluor replacement), U-SHAPE & CIRCULAR LAMPS				
	Туре	Linear, Single Ended, Instant Start				
Pa	ckaging					
	Carton	25				

0.72

Food Equipment, Splash Zone, Dry and Damp Location

UL (Canada and US), UL, NSF/ANSI, DLC