

troffer

0 F F I C E R E T A I L S C H 0 O L

EASY on the budget

LJT is rebate friendly for attainable LED lighting. Projects will run smoothly and stay on track within your resources.

EASY to use rebates

Take advantage of utility rebates for even greater cost effectiveness.

- 2x4—Save up to 32% energy
- 2x2—Save up to 38% energy
- DesignLights Consortium® qualified

EASY on the **CONTRACTOR**

LJT is designed as a one-for-one replacement for fluorescent lensed troffers.

- 2x4, 2x2
- Grid, surface, or cable mount

EASY on the project

LJT offers on/off, step-dimming, 0-10V continuous dimming, flex, integral emergency battery pack, IC rating and all the options you need to make the project work.

EASY on the distributor

LJT is stocked in the Hubbell Lighting Regional Distribution Centers.

EASY on the OWNER

Change your lamps only **once every 12 years** with LJT's 50,000 hour rated life*.

- L70 lumen maintenance
- 4 LED color choices with excellent color consistency and 82 CRI
- 5 year warranty







ONE-FOR-ONE FIXTURE REPLACEMENT









QUALITY ASSURANCE

Each LJT is rigorously tested for quality before it ships. If it doesn't pass, it doesn't ship.

A unique QR Code is affixed to each housing, providing a permanent record of product details for future upgrades or replacement. 5 year warranty. Terms and conditions apply.



LED PERFORMANCE

Stay off the ladder. Long-life LEDs rated at 50,000 hours and L70 lumen maintenance reduce facility maintenance. Plus, LJT has excellent color consistency, access to LED boards and driver from below the ceiling, and modular replaceability. LJT provides good lighting today, tomorrow and for years to come.

ORDERING INFORMATION

							U	J- L	
MODEL COLOR TEMP (CEILING TYPE	SHI	ELDING		DRIVER	1	VOLTAGE		OPTIONS
40 4000K	G Grid¹ SM Surface Mount CM Cable Mount²		Pattern 12 Acrylic Lens Pattern 12 Acrylic Lens, 0.125" Nominal	ESD	Fixed Output Step Dimming 0-10V Dimming	U	120V-277V	C488 C588	3-Wire Flex 4-Wire Flex 5-Wire Flex Emergency Battery Pack, 1400 Lumens, Installed ^{3,4}
SIZE LUMEN OUT	PUT	A12F	Pattern 12					GLR	Fast Blow Fuse
22 2' x 2' LW Low Watt (2x4 24 2' x 4' ML Medium Lume	3,		Frosted Acrylic Lens						Single Gasketing (Door to Housing)
HL High Lumen (A12125F	Pattern 12 Frosted Acrylic					G2	Double Gasketing (G1 and Lens to Door)
See Product Availability	table below.	_	Lens, 0.125" Nominal					G3	Triple Gasketing (G2 and Housing to Ceiling)
	DOOR FS White Flush Steel	A19	Pattern 19 Acrylic Lens, 0.156" Nominal					WIH	wiHUBB ^{5,6}
	FA White Flush Aluminum For more door options contact	A19F	Pattern 19 Frosted Acrylic Lens .156"						

- ¹ For hard ceilings use flange kit accessory.
- ² Order hanger accessories separately.
- ³ For compatibility with Dual-Lite LiteGear[®] inverters in lieu of EL Battery Pack, contact Hubbell Lighting Representative.
- 4 Not available with 2x2 Surface or Cable Mount.
- ⁵ Not available with Surface Mount ceiling types.
- $^{\rm 6}$ In-Fixture Module Antenna adds 2" to overall fixture height at power feed location.

Damp Label - standard. IC Rating - standard.

Product Availability — Nominal Lumens					
Size	LW	ML	HL		
2 x 2	_	3200	4000		
2 x 4	4100	5000	_		

	ESSORIES SEPARATELY)
FK22	2' × 2' Single Flange Ki
FK24	2' x 4' Single Flange Ki
FKCR	Flange Kit Row Adaptor (All Sizes)

CM48Y2SC3F-KIT

48" Cable Mount Kit for 2' Wide CM Ceiling Type, 3 Wire Feed Cord

factory.





troffer

0 F F I C E R E T A I L S C H 0 O L

EASY on the budget

LJT is rebate friendly for attainable LED lighting. Projects will run smoothly and stay on track within your resources.

EASY to use rebates

Take advantage of utility rebates for even greater cost effectiveness.

- 2x4—Save up to 32% energy
- 2x2—Save up to 38% energy
- DesignLights Consortium® qualified

EASY on the **CONTRACTOR**

LJT is designed as a one-for-one replacement for fluorescent lensed troffers.

- 2x4, 2x2
- Grid, surface, or cable mount

EASY on the project

LJT offers on/off, step-dimming, 0-10V continuous dimming, flex, integral emergency battery pack, IC rating and all the options you need to make the project work.

EASY on the distributor

LJT is stocked in the Hubbell Lighting Regional Distribution Centers.

EASY on the OWNER

Change your lamps only **once every 12 years** with LJT's 50,000 hour rated life*.

- L70 lumen maintenance
- 4 LED color choices with excellent color consistency and 82 CRI
- 5 year warranty







ONE-FOR-ONE FIXTURE REPLACEMENT









QUALITY ASSURANCE

Each LJT is rigorously tested for quality before it ships. If it doesn't pass, it doesn't ship.

A unique QR Code is affixed to each housing, providing a permanent record of product details for future upgrades or replacement. 5 year warranty. Terms and conditions apply.



LED PERFORMANCE

Stay off the ladder. Long-life LEDs rated at 50,000 hours and L70 lumen maintenance reduce facility maintenance. Plus, LJT has excellent color consistency, access to LED boards and driver from below the ceiling, and modular replaceability. LJT provides good lighting today, tomorrow and for years to come.

ORDERING INFORMATION

							U	J- L	
MODEL COLOR TEMP (CEILING TYPE	SHI	ELDING		DRIVER	1	VOLTAGE		OPTIONS
40 4000K	G Grid¹ SM Surface Mount CM Cable Mount²		Pattern 12 Acrylic Lens Pattern 12 Acrylic Lens, 0.125" Nominal	ESD	Fixed Output Step Dimming 0-10V Dimming	U	120V-277V	C488 C588	3-Wire Flex 4-Wire Flex 5-Wire Flex Emergency Battery Pack, 1400 Lumens, Installed ^{3,4}
SIZE LUMEN OUT	PUT	A12F	Pattern 12					GLR	Fast Blow Fuse
22 2' x 2' LW Low Watt (2x4 24 2' x 4' ML Medium Lume	3,		Frosted Acrylic Lens						Single Gasketing (Door to Housing)
HL High Lumen (A12125F	Pattern 12 Frosted Acrylic					G2	Double Gasketing (G1 and Lens to Door)
See Product Availability	table below.	_	Lens, 0.125" Nominal					G3	Triple Gasketing (G2 and Housing to Ceiling)
	DOOR FS White Flush Steel	A19	Pattern 19 Acrylic Lens, 0.156" Nominal					WIH	wiHUBB ^{5,6}
	FA White Flush Aluminum For more door options contact	A19F	Pattern 19 Frosted Acrylic Lens .156"						

- ¹ For hard ceilings use flange kit accessory.
- ² Order hanger accessories separately.
- ³ For compatibility with Dual-Lite LiteGear[®] inverters in lieu of EL Battery Pack, contact Hubbell Lighting Representative.
- 4 Not available with 2x2 Surface or Cable Mount.
- ⁵ Not available with Surface Mount ceiling types.
- $^{\rm 6}$ In-Fixture Module Antenna adds 2" to overall fixture height at power feed location.

Damp Label - standard. IC Rating - standard.

Product Availability — Nominal Lumens					
Size	LW	ML	HL		
2 x 2	_	3200	4000		
2 x 4	4100	5000	_		

	ESSORIES SEPARATELY)
FK22	2' × 2' Single Flange Ki
FK24	2' x 4' Single Flange Ki
FKCR	Flange Kit Row Adaptor (All Sizes)

CM48Y2SC3F-KIT

48" Cable Mount Kit for 2' Wide CM Ceiling Type, 3 Wire Feed Cord

factory.

