

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Packaging

Carton

Weight Per each

LL125M 1-1/4" LL FM5 Conduit Body

| Catalog Number | LL125M | |
|----------------------------------|---|--|
| Manufacturer | Crouse-Hinds | |
| Description | Conduit Body, Electrogalvanized With Aluminum Acrylic Paint, Form 5 Body Type, 1-1/4 In Trade Size, Threaded Connection, LL Shape, Left Side Cable Entry, 2 Hubs, 1-1/4 In Hub Size, 90° Hub Location, LL Configuration, 8.12 In Length, 2.75 In Width, 2.75 In Height, Threaded, 2.62 LB/Ea | |
| Weight per unit | 2.6 (lbs/each) | |
| Product Category | Bodies & Covers | |
| Features | | |
| dimensions | 8.1200 IN X 2.7500 IN X 2.7500 IN | |
| Form | Form 5 | |
| Dimensions and Weight | | |
| Height | 2.75 | |
| Hub Size | 1-1/4 in | |
| Width | 2.75 | |
| Descriptions | | |
| D escription | 1-1/4" LL FM5 CONDUIT BODY | |
| extra long description | CRS-H LL125M 1 1/4 FORM 5 LL COND B | |
| Features | Form 5 malleable iron conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide access to conductors for maintenance and future system changes. Form 5 conduit bodies are manufactured in trade sizes 1/2" to 4", and are interchangeable with Appleton Form 35 conduit bodies. They are also available with a h | |
| Manufacturer Information | | |
| Brand | Eaton | |
| GTIN | 00782274756165 | |
| UPC | 782274756165 | |
| Taxonomies, Classifications, and | | |
| Category Description | | |
| Туре | Conduit outlet body | |

5

2.62

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Uses, Certificat | tions, and | l Stand | ards |
|------------------|------------|---------|------|
|------------------|------------|---------|------|

standard UL 514B, CSA C22.2, CUL